



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 20

LOCTITE LB 8030 known as Loctite 8030 250ml EGFD

SDS No. : 362689
V003.0

Revision: 17.03.2023

printing date: 20.03.2023

Replaces version from: 14.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE LB 8030 known as Loctite 8030 250ml EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Lubricant

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

|| Skin sensitizer Category 1
|| H317 May cause an allergic skin reaction.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Polysulfides, di-tert-dodecyl

Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate

Sulfonic acids, petroleum, calcium salts

Signal word:	Warning
Hazard statement:	H317 May cause an allergic skin reaction.
Precautionary statement: Prevention	P280 Wear protective gloves.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8 265-158-7 01-2119487077-29	50- 100 %	Asp. Tox. 1, H304		
White mineral oil (petroleum) 8042-47-5 232-455-8 01-2119487078-27	10- 20 %	Asp. Tox. 1, H304		
Polysulfides, di-tert-dodecyl 68425-15-0 270-335-7 01-2119540516-41	5- < 10 %	Aquatic Chronic 4, H413 Skin Sens. 1B, H317		
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0 276-159-7 01-2120770937-38	0,1- < 1 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317 Flam. Liq. 3, H226	oral:ATE = 2.500 mg/kg	
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6 271-529-4 01-2119492627-25	0,1- < 1 %	Skin Sens. 1B, H317	Skin Sens. 1B; H317; C >= 10 %	
Sulfonic acids, petroleum, calcium salts 61789-86-4 263-093-9 01-2119488992-18	0,1- < 1 %	Skin Sens. 1B, H317		
(C16-C24)Alkylbenzenesulfonic acid, Ca 70024-69-0 274-263-7 01-2119492616-28	0,1- < 1 %	Skin Sens. 1B, H317	Skin Sens. 1B; H317; C >= 10 %	

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Do not induce vomiting.

Seek medical attention from a specialist.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin and eye contact.

Ensure adequate ventilation.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

See advice in section 8

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.
Keep away from heat and direct sunlight.
Refer to Technical Data Sheet

7.3. Specific end use(s)

Lubricant

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
White mineral oil (petroleum) 8042-47-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
White mineral oil (petroleum) 8042-47-5		5	Exposure limit(s):	4 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Polysulfides, di-tert-dodecyl 68425-15-0			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Polysulfides, di-tert-dodecyl 68425-15-0		5	Exposure limit(s):	4 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Calcium carbonate 471-34-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Calcium carbonate 471-34-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Sulfonic acids, petroleum, calcium salts 61789-86-4		5	Exposure limit(s):	4	TRGS 900
Sulfonic acids, petroleum, calcium salts 61789-86-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	oral				9,33 mg/kg		
White mineral oil (petroleum) 8042-47-5	Air						no hazard identified
Polysulfides, di-tert-dodecyl 68425-15-0	sewage treatment plant (STP)		1000 mg/l				
Polysulfides, di-tert-dodecyl 68425-15-0	oral				66,7 mg/kg		
Polysulfides, di-tert-dodecyl 68425-15-0	sediment (freshwater)				3,85 mg/kg		
Polysulfides, di-tert-dodecyl 68425-15-0	sediment (marine water)				0,385 mg/kg		
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	aqua (freshwater)		0,00255 mg/l				
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	aqua (marine water)		0,000255 mg/l				
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	Freshwater - intermittent		0,0255 mg/l				
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	sediment (freshwater)				0,794 mg/kg		
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	sediment (marine water)				0,0794 mg/kg		
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	sewage treatment plant (STP)		0,00035 mg/l				
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	Soil				0,157 mg/kg		
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	Marine water - intermittent		0,00255 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	General population	inhalation	Long term exposure - local effects		1,19 mg/m ³	
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	Workers	inhalation	Long term exposure - local effects		5,58 mg/m ³	
White mineral oil (petroleum) 8042-47-5	Workers	Inhalation	Long term exposure - systemic effects		160 mg/m ³	no hazard identified
White mineral oil (petroleum) 8042-47-5	Workers	dermal	Long term exposure - systemic effects		220 mg/kg	no hazard identified
White mineral oil (petroleum) 8042-47-5	General population	dermal	Long term exposure - systemic effects		93 mg/kg	no hazard identified
White mineral oil (petroleum) 8042-47-5	General population	Inhalation	Long term exposure - systemic effects		35 mg/m ³	no hazard identified
White mineral oil (petroleum) 8042-47-5	General population	oral	Long term exposure - systemic effects		40 mg/kg	no hazard identified
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	Workers	inhalation	Long term exposure - systemic effects		4,28 mg/m ³	
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	Workers	dermal	Long term exposure - systemic effects		0,607 mg/kg	
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	General population	inhalation	Long term exposure - systemic effects		0,754 mg/m ³	
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	General population	dermal	Long term exposure - systemic effects		0,217 mg/kg	
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	General population	oral	Long term exposure - systemic effects		0,217 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	Currently under determination
Colour	Yellow
Odor	Characteristic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Initial boiling point	Currently under determination
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	Currently under determination
Auto-ignition temperature	Currently under determination
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Currently under determination
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	Mixture
Density	Currently under determination
()	0,884 - 0,944 g/cm ³ None
Relative vapour density:	Currently under determination
Particle characteristics	Not applicable
	Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Irritating organic vapours.

SECTION 11: Toxicological information**General toxicological information:**

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
White mineral oil (petroleum) 8042-47-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Polysulfides, di-tert- dodecyl 68425-15-0	LD0	> 2.000 mg/kg	rat	other guideline:
Polysulfides, di-tert- dodecyl 68425-15-0	LD50	> 2.000 mg/kg	rat	other guideline:
Amines, C12-14-tert- alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Amines, C12-14-tert- alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
White mineral oil (petroleum) 8042-47-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Polysulfides, di-tert- dodecyl 68425-15-0	LD0	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Polysulfides, di-tert- dodecyl 68425-15-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
White mineral oil (petroleum) 8042-47-5	LC50	> 5 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not irritating	24 h	rabbit	not specified
White mineral oil (petroleum) 8042-47-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Polysulfides, di-tert- dodecyl 68425-15-0	mildly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
White mineral oil (petroleum) 8042-47-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)
(C16-C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
White mineral oil (petroleum) 8042-47-5	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Polysulfides, di-tert-dodecyl 68425-15-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Sulfonic acids, petroleum, calcium salts 61789-86-4	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
(C16-C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
White mineral oil (petroleum) 8042-47-5	negative	bacterial reverse mutation assay (e.g Ames test)	with		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
White mineral oil (petroleum) 8042-47-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
White mineral oil (petroleum) 8042-47-5	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
White mineral oil (petroleum) 8042-47-5	NOAEL P \geq 2.000 mg/kg NOAEL F1 \geq 2.000 mg/kg	one- generation study	dermal	rat	OECD Guideline 415 (One- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
White mineral oil (petroleum) 8042-47-5	NOAEL \geq 1.600 mg/kg	oral: feed	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	NOAEL 500 mg/kg	oral: gavage	29 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOAEL 1.000 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	NOAEL 500 mg/kg	oral: gavage	29 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	17,2 mm ² /s	40 °C	DIN EN ISO 3104	
White mineral oil (petroleum) 8042-47-5	ca. 3,8 mm ² /s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	NOEC	> 5.000 mg/l	7 d	Pimephales promelas	not specified
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LC50	> 5.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
White mineral oil (petroleum) 8042-47-5	LL50	> 100 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Polysulfides, di-tert-dodecyl 68425-15-0	LC50	Toxicity > Water solubility		Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Amines, C12-14-tert-alkyl, reaction products with O,O-di- C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	LC50	2,55 mg/l	96 h	Danio rerio	EU Method C.1 (Acute Toxicity for Fish)
Benzenesulfonic acid, C10- 16-alkyl derivs., calcium salts 68584-23-6	LL50	> 10.000 mg/l	96 h	Cyprinodon variegatus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LL50	> 1.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	LC50	Toxicity > Water solubility	96 h	Cyprinodon variegatus	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	EL50	> 10.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
White mineral oil (petroleum) 8042-47-5	EL50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Amines, C12-14-tert-alkyl, reaction products with O,O-di- C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	EL50	4,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6	EC50	> 1.000 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 1.000 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
(C16-	EC50	Toxicity > Water	48 h	Daphnia magna	EPA OTS 797.1300

C24)Alkybenzenesulfonic acid, Ca 70024-69-0		solubility			(Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
--	--	------------	--	--	---

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	NOELR	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
White mineral oil (petroleum) 8042-47-5	NOEL	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
White mineral oil (petroleum) 8042-47-5	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Polysulfides, di-tert-dodecyl 68425-15-0	NOEC	Toxicity > Water solubility		Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, C12-14-tert-alkyl, reaction products with O,O-di- C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	EL50	3,9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, C12-14-tert-alkyl, reaction products with O,O-di- C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	NOELR	0,32 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6	EC50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6	NOEC	1.000 mg/l	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
White mineral oil (petroleum) 8042-47-5	IC50	> 100 mg/l	93 d	other:	other guideline:
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 10.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	EC50	> 10.000 mg/l	3 h	activated sludge of a predominantly industrial sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The product is not biodegradable.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not readily biodegradable.	aerobic	31 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
White mineral oil (petroleum) 8042-47-5	not readily biodegradable.	aerobic	31,3 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Polysulfides, di-tert-dodecyl 68425-15-0		aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Amines, C12-14-tert-alkyl, reaction products with O,O-di- C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

No substance data available.

12.4. Mobility in soil

The product evaporates readily.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
White mineral oil (petroleum) 8042-47-5	> 4		EU Method A.8 (Partition Coefficient)
Polysulfides, di-tert-dodecyl 68425-15-0	12,46		not specified
Amines, C12-14-tert-alkyl, reaction products with O,O-di- C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	4,8	23 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Sulfonic acids, petroleum, calcium salts 61789-86-4	22,12	25 °C	QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
White mineral oil (petroleum) 8042-47-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Polysulfides, di-tert-dodecyl 68425-15-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate 71888-91-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Sulfonic acids, petroleum, calcium salts 61789-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
(C16-C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 10

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.