

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 23

TEROSON WX 400

SDS No. : 456436 V017.0 Revision: 26.01.2024 printing date: 30.01.2024 Replaces version from: 05.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1. Product identifier** TEROSON WX 400
- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use:

Cavity sealing

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA Henkelstr. 67 40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):	
Flammable liquids	Category 3
H226 Flammable liquid and vapour.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:	
Contains	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	Sulfonic acids, petroleum, calcium salts
	Rape oil, reaction products with diethylenetriamine
Signal word:	Warning
Hazard statement:	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Supplemental information	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statement: Prevention	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.No smoking.P261 Avoid breathing vapors.P273 Avoid release to the environment.P280 Wear protective gloves.
Precautionary statement: Response	P370+P378 In case of fire: Use CO2, dry chemical, or foam for extinction.
Precautionary statement: Storage	P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	S-No. umber		Specific Conc. Limits, M- factors and ATEs	Add. Information
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9 01-2119463258-33	20- 40 %	Asp. Tox. 1, H304 Flam. Liq. 3, H226 STOT SE 3, H336		
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119463258-33	10- < 20 %	Asp. Tox. 1, H304 Flam. Liq. 3, H226 STOT SE 3, H336		
Sulfonic acids, petroleum, calcium salts 61789-86-4 263-093-9 01-2119488992-18	5- < 10 %	Skin Sens. 1B, H317		
Mineral oil mix 01-2119471299-27 01-2119480132-48 01-2119484627-25 01-2119487077-29	5- < 10 %	Asp. Tox. 1, H304		
Distillates (petroleum), solvent- refined light paraffinic, < 3%DMSO 64741-89-5 265-091-3 01-2119487067-30	1- < 5 %	Asp. Tox. 1, H304		
Rape oil, reaction products with diethylenetriamine 91081-13-9 293-615-0 01-2120743155-59	1- < 3 %	Skin Sens. 1B, H317	oral:ATE = 2.500 mg/kg	
Distillates (petroleum), solvent- dewaxed heavy paraffinic < 3%DMSO 64742-65-0 265-169-7 01-2119471299-27	1-< 3 %	Asp. Tox. 1, H304		
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm²/sec (not cmr) 64742-54-7 265-157-1 01-2119484627-25	1- < 3 %	Asp. Tox. 1, H304		
Nonane 111-84-2 203-913-4	1- < 2,5 %	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
oleic acid, compound with (Z)-N- octadec-9-enylpropane-1,3- diamine (2:1) 34140-91-5 251-846-4 01-2119974119-29	0,1- < 1 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M acute = 10 ===== oral:ATE = 2.500 mg/kg	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Move to fresh air, consult doctor if complaint persists.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. In case of adverse health effects seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed SKIN: Rash, Urticaria.

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media: Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons: Water jet (solvent-containing product).

5.2. Special hazards arising from the substance or mixture In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus. Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Avoid contact with skin and eyes. Keep unprotected persons away. Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water. Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust). Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid open flames and sources of ignition. Ground/bond container and receiving equipment. Use explosion proof electric equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Hygiene measures:

Do not eat, drink or smoke while working. Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Storage at 5 to 25°C is recommended.

7.3. Specific end use(s)

Cavity sealing

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list	
Sulfonic acids, petroleum, calcium salts 61789-86-4		5	Exposure limit(s):	4	TRGS 900	
Sulfonic acids, petroleum, calcium salts 61789-86-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900	
Calcium carbonate 471-34-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900	
Calcium carbonate 471-34-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900	
Calcium carbonate 471-34-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900	
Nonane 111-84-2		600	Exposure limit(s):	2	TRGS 900	
Nonane 111-84-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900	

V017.0

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value		Remarks		
			mg/l	ppm	mg/kg	others	
Sulfonic acids, petroleum, calcium salts 61789-86-4	aqua (freshwater)		1,00 mg/l				
Sulfonic acids, petroleum, calcium salts 61789-86-4	aqua (marine water)		1,0 mg/l				
Sulfonic acids, petroleum, calcium salts 61789-86-4	sewage treatment plant (STP)		1000,00 mg/l				
Mineral oil mix	oral				9,33 mg/kg		
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	oral				9,33 mg/kg		
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	oral				9,33 mg/kg		
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	oral				9,33 mg/kg		
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	aqua (freshwater)		0,00646 mg/l				
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	Freshwater - intermittent		0,0041 mg/l				
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	aqua (marine water)		0,000646 mg/l				
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	sediment (freshwater)				388 mg/kg		
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	sediment (marine water)				38,8 mg/kg		
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	Soil				9,93 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C9-C11, n-alkanes,	Workers	dermal	Long term		300 mg/kg	
isoalkanes, cyclics, < 2% aromatics 64742-48-9			exposure - systemic effects			
Hydrocarbons, C9-C11, n-alkanes,	Workers	Inhalation	Long term		1500 mg/m3	
isoalkanes, cyclics, < 2% aromatics			exposure -		C	
64742-48-9	General	.1	systemic effects		200	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	population	dermal	Long term exposure -		300 mg/kg	
64742-48-9	1 1		systemic effects			
Hydrocarbons, C9-C11, n-alkanes,	General	Inhalation	Long term		900 mg/m3	
isoalkanes, cyclics, < 2% aromatics 64742-48-9	population		exposure - systemic effects			
Hydrocarbons, C9-C11, n-alkanes,	General	oral	Long term		300 mg/kg	
isoalkanes, cyclics, < 2% aromatics	population		exposure -			
64742-48-9 Hydrocarbons, C9-C11, n-alkanes,	XX 71	Tub slation	systemic effects		971	
isoalkanes, cyclics, < 2% aromatics	Workers	Inhalation	Long term exposure -		871 mg/m3	
			systemic effects			
Hydrocarbons, C9-C11, n-alkanes,	Workers	dermal	Long term		77 mg/kg	
isoalkanes, cyclics, < 2% aromatics			exposure - systemic effects			
Hydrocarbons, C9-C11, n-alkanes,	General	Inhalation	Long term		185 mg/m3	
isoalkanes, cyclics, < 2% aromatics	population		exposure -		-	
	Concert		systemic effects		46	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	General population	dermal	Long term exposure -		46 mg/kg	
	population		systemic effects			
Hydrocarbons, C9-C11, n-alkanes,	General	oral	Long term		46 mg/kg	
isoalkanes, cyclics, < 2% aromatics	population		exposure - systemic effects			
Mineral oil mix	General	inhalation	Long term		1,2 mg/m3	
	population		exposure - local		, ,	
	337 1	. 1 . 1	effects		5.6 (2	
Mineral oil mix	Workers	inhalation	Long term exposure - local		5,6 mg/m3	
			effects			
Mineral oil mix	Workers	inhalation	Long term		2,7 mg/m3	
			exposure - systemic effects			
Mineral oil mix	General	oral	Long term		0,74 mg/kg	
	population		exposure -			
Mineral oil mix	Workers	dermal	systemic effects Long term		1 mg/kg	
	workers	uermai	exposure -		1 mg/kg	
			systemic effects			
Distillates (petroleum), solvent-refined light	Workers	inhalation	Long term		5,58 mg/m3	
paraffinic, < 3%DMSO 64741-89-5			exposure - local effects			
Distillates (petroleum), solvent-refined light	General	inhalation	Long term		1,2 mg/m3	
paraffinic, < 3% DMSO	population		exposure - local			
64741-89-5 Distillates (petroleum), solvent-refined light	Workers	inhalation	effects Long term		5,4 mg/m3	
paraffinic, < 3%DMSO	WOIKEIS	minatation	exposure -		J,+ mg/mJ	
64741-89-5			systemic effects			
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	Workers	inhalation	Long term		2,7 mg/m3	
64742-65-0			exposure - systemic effects			
Distillates (petroleum), solvent-dewaxed	Workers	inhalation	Long term		5,6 mg/m3	
heavy paraffinic < 3%DMSO			exposure - local			
64742-65-0 Distillates (petroleum), solvent-dewaxed	Workers	dermal	effects Long term		0,97 mg/kg	
heavy paraffinic < 3%DMSO	TOINCIS	uerman	exposure -		5,27 mg/kg	
64742-65-0			systemic effects			
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	General	oral	Long term		0,74 mg/kg	
64742-65-0	population		exposure - systemic effects			
Distillates (petroleum), hydrotreated heavy	Workers	inhalation	Long term		5,4 mg/m3	
paraffinic, <3% DMSO, <20.5mm ² /sec (not			exposure - local			

SDS No.: 456436 V017.0

cmr) 64742-54-7			effects		
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	Workers	inhalation	Long term exposure - systemic effects	0,0984 mg/m3	
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	Workers	dermal	Long term exposure - systemic effects	0,014 mg/kg	
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	General population	inhalation	Long term exposure - systemic effects	0,0174 mg/m3	
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	General population	dermal	Long term exposure - systemic effects	0,005 mg/kg	
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	General population	oral	Long term exposure - systemic effects	0,005 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls: Use only in well ventilated areas.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection: Goggles which can be tightly sealed. Protective eye equipment should conform to EN166.

Skin protection: Wear protective equipment. Protective clothing that covers arms and legs. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form Colour Odor Physical state Melting point liquid brown hydrocarbons liquid Not applicable, Product is a liquid

SDS No.: 456436 V017.0

lower

upper

pН

Solidification temperature < -50 °C (< -58 °F) Initial boiling point 154 °C (309.2 °F) Flammability Flammable liquid Explosive limits 0,6 %(V); No data available. 6,5 %(V); No data available. Upper/lower explosion limit 43 °C (109.4 °F); DIN 51755 Closed cup flash point Flash point Auto-ignition temperature > 237 °C (> 458.6 °F) Decomposition temperature Not applicable, Product is non-soluble (in water). Viscosity (kinematic) 140 mm2/s ;.Supplier method (40 °C (104 °F);) Viscosity, dynamic 130 mPa.s no method / method unknown (; 40 °C (104 °F); speed of rotation: 100,0 min-1) Flow cup viscosity 18 s DIN EN ISO 2431 Running out time with flow cups (20 °C (68 °F); Type of cup: DIN-Cup; Nozzle: 4 mm DIN EN ISO 2431; QP2017.1, QP1580.0; Running out time with flow cups) Flow cup viscosity 34 s DIN EN ISO 2431 Running out time with flow cups (23,0 °C (73.4 °F); Type of cup: DIN-Cup; Nozzle: 3,0 mm DIN EN ISO 2431; OP2017.1, QP1580.0; Running out time with flow cups) Not miscible Solubility (qualitative) (20 °C (68 °F); Solvent: Water) Partition coefficient: n-octanol/water Not applicable Mixture 4900 Pa Vapour pressure (50 °C (122 °F)) Vapour pressure 1500 Pa (55 °C (131 °F)) Vapour pressure 960 Pa (20 °C (68 °F)) 0,885 - 0,915 g/cm3 (20 °C (68 °F)) Relative vapour density: 1,16 Particle characteristics Not applicable Product is a liquid

9.2. Other information

Density

(20 °C)

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity Oxidizers.

10.2. Chemical stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Rape oil, reaction products with diethylenetriamine 91081-13-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Rape oil, reaction products with diethylenetriamine 91081-13-9	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Nonane 111-84-2	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value	Value	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	type LD50	> 5.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LD50	> 5.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Rape oil, reaction products with diethylenetriamine 91081-13-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Nonane 111-84-2	LD50	> 2.000 mg/kg	rabbit	not specified
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LC50	> 5,6 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LC50	> 9,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50	> 5,6 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50	> 9,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	mildly irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	mildly irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)
Rape oil, reaction products with diethylenetriamine 91081-13-9	not corrosive	60 min	Human, EpiDermTM SIT (EPI-200), Reconstructed Human Epidermis (RHE)	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
Rape oil, reaction products with diethylenetriamine 91081-13-9	not irritating	15 min	Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not irritating	24 h	rabbit	not specified
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO,	not irritating	24 h	rabbit	not specified

<20.5mm ² /sec (not cmr) 64742-54-7				
Nonane 111-84-2	irritating	rabbit	Weight of evidence	
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	irritating	rabbit	Weight of evidence	

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)
Rape oil, reaction products with diethylenetriamine 91081-13-9	not irritating	240 min	Bovine, cornea, in vitro test	OECD Guideline 437 (BCOP)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Rape oil, reaction products with diethylenetriamine 91081-13-9	Sub-Category 1B (sensitising)	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Rape oil, reaction products with diethylenetriamine 91081-13-9	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Rape oil, reaction products with diethylenetriamine 91081-13-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Rape oil, reaction products with diethylenetriamine 91081-13-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 490 (In Vitro Mammalian Cell Gene Mutation Tests Using the Thymidine Kinase Gene)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not carcinogenic	dermal	78 w various	mouse	female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

No data available.

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Assessment	Route of	Target Organs	Remarks
CAS-No.		exposure		
Hydrocarbons, C9-C11,	Category 3 with narcotic effects.			
n-alkanes, isoalkanes,				
cyclics, < 2% aromatics				
Nonane	Category 3 with narcotic effects.			
111-84-2				

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOAEL 1.000 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Rape oil, reaction products with diethylenetriamine 91081-13-9	NOAEL 1.000 mg/kg	oral: gavage	42 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	1,02 mm2/s	40 °C	calculated	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	0 mm2/s	40 °C	not specified	
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	11 mm2/s	40 °C		
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	20 mm2/s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	LL50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	LL50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LL50	> 1.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Mineral oil mix	LC50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	LC50	> 1.000 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Rape oil, reaction products with diethylenetriamine 91081-13-9	LL50	> 100 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	LC50	> 5.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	LL50	> 100 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
oleic acid, compound with (Z)-N-octadec-9-enylpropane- 1,3-diamine (2:1) 34140-91-5	LC50	0,135 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 1.000 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)

SDS No.: 456436
V017.0

Mineral oil mix	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Rape oil, reaction products with diethylenetriamine 91081-13-9	EL50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	EL50	> 10.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Nonane 111-84-2	EC50	0,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_	-	
Distillates (petroleum),	NOEC	1.000 mg/l	21 d	1 0	OECD 211 (Daphnia
solvent-refined light paraffinic, < 3%DMSO					magna, Reproduction Test)
64741-89-5					
Distillates (petroleum),	NOEC	> 1.000 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
solvent-dewaxed heavy					magna, Reproduction Test)
paraffinic < 3%DMSO 64742-65-0					
Distillates (petroleum),	NOELR	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
hydrotreated heavy paraffinic,		i o ing i			magna, Reproduction Test)
<3% DMSO, <20.5mm ² /sec					
(not cmr)					
64742-54-7					
oleic acid, compound with	EC10	0,136 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
(Z)-N-octadec-9-enylpropane-					magna, Reproduction Test)
1,3-diamine (2:1)					
34140-91-5					

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Mineral oil mix	EC50	1.100 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	,
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Rape oil, reaction products with diethylenetriamine 91081-13-9	EL50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Rape oil, reaction products with diethylenetriamine 91081-13-9	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	EL50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
oleic acid, compound with (Z)-N-octadec-9-enylpropane- 1,3-diamine (2:1) 34140-91-5	EC50	0,041 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
oleic acid, compound with (Z)-N-octadec-9-enylpropane- 1,3-diamine (2:1) 34140-91-5	EC10	0,0323 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 10.000 mg/l		predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Mineral oil mix	EC50	> 1.000 mg/l	3 h	0	OECD Guideline 209 (Activated Sludge,

					Respiration Inhibition Test)
Rape oil, reaction products	EC50	> 1.000 mg/l	3 h	activated sludge of a	OECD Guideline 209
with diethylenetriamine				predominantly domestic sewage	(Activated Sludge,
91081-13-9					Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	readily biodegradable	aerobic	80 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	readily biodegradable	aerobic	80 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Mineral oil mix	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Distillates (petroleum), solvent-refined light paraffinic, < 3% DMSO 64741-89-5	not readily biodegradable.	aerobic	22 - 29 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Rape oil, reaction products with diethylenetriamine 91081-13-9	readily biodegradable	aerobic	71 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not readily biodegradable.	aerobic	6 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	not readily biodegradable.	aerobic	31 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Nonane 111-84-2	readily biodegradable	aerobic	100 %	25 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
oleic acid, compound with (Z)-N-octadec-9-enylpropane- 1,3-diamine (2:1) 34140-91-5	readily biodegradable	aerobic	61 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Sulfonic acids, petroleum, calcium salts 61789-86-4	22,12	25 °C	QSAR (Quantitative Structure Activity Relationship)
Mineral oil mix	10,88		EU Method A.8 (Partition Coefficient)
Nonane 111-84-2	5,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
oleic acid, compound with (Z)-N-octadec-9-enylpropane- 1,3-diamine (2:1) 34140-91-5	0,03	25,7 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow- Stirring Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Sulfonic acids, petroleum, calcium salts 61789-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Distillates (petroleum), solvent-refined light paraffinic, < 3%DMSO 64741-89-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO, <20.5mm ² /sec (not cmr) 64742-54-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Nonane 111-84-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1) 34140-91-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

14.1.	UN number or ID number
19.1.	

ADR	1139
RID	1139
ADN	1139
IMDG	1139
IATA	1139

14.2. UN proper shipping name

ADR	COATING SOLUTION
RID	COATING SOLUTION
ADN	COATING SOLUTION
IMDG	COATING SOLUTION
IATA	Coating solution

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Persistent organic pollutants (Regulation (EU) 2019/1021): VOC content 41,9 %

TEROSON WX 400

(2010/75/EU)

Not applicable

VOC Paints and Varnishes (EU):

Regulatory Basis: Product (sub)category: Phase I (from 1.1.2007): max. VOC content: Directive 2004/42/EC B(e) Special finishes 840 g/l 366,7 g/l

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

National regulations/information (Germany):

WGK:

WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)

Not applicable

Not applicable

BG regulations, rules, infos:

```
BG data sheet: BGI 621 Solvents
0: 3
```

Storage class according to TRGS 510:

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.