



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 26

TEROSON SB 2444

SDS No. : 76601  
V017.0

Revision: 03.02.2023  
printing date: 09.02.2023

Replaces version from: 06.07.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TEROSON SB 2444

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Contact adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

SDSinfo.Adhesive@henkel.com

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Acute hazards to the aquatic environment	Category 1
H400 Very toxic to aquatic life.	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

**2.2. Label elements****Label elements (CLP):****Hazard pictogram:****Contains**

cyclohexane

Ethyl acetate

Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol

rosin

**Signal word:**

Danger

**Hazard statement:**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

**Precautionary statement:  
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapors.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection.

**Precautionary statement:  
Response**P370+P378 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.**Precautionary statement:  
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
cyclohexane 110-82-7 203-806-2 01-2119463273-41	20- 40 %	Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Flam. Liq. 2, H225 Skin Irrit. 2, H315	M acute = 1 M chronic = 1	EU OEL
Ethyl acetate 141-78-6 205-500-4 01-2119475103-46	20- 40 %	Flam. Liq. 2, H225 STOT SE 3, H336 Eye Irrit. 2, H319		EU OEL
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0 927-510-4 01-2119475515-33	10- < 20 %	Aquatic Chronic 2, H411 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Flam. Liq. 2, H225 STOT SE 3, H336	inhalation:ATE = 23,31 mg/l;vapour	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0 931-254-9 01-2119484651-34	1- < 5 %	Skin Irrit. 2, H315 Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411		
Formaldehyde, polymer with 4- (1,1-dimethylethyl)phenol 25085-50-1	1- < 5 %	Skin Sens. 1, H317		
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0 926-605-8 01-2119486291-36	1- < 3 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411		
rosin 8050-09-7 232-475-7 01-2119480418-32	1- < 3 %	Skin Sens. 1, H317		
zinc oxide 1314-13-2 215-222-5 01-2119463881-32	0,25- < 2,5 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Disulfiram 97-77-8 202-607-8	0,01- < 0,1 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Inhalation, H332 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 STOT RE 2, H373	M acute = 10 M chronic = 10 ===== oral:ATE = 1.861 mg/kg	

**For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.**

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

**Skin contact:**

IF ON SKIN: Wash with plenty of soap and water.  
In case of adverse health effects seek medical advice.

**Eye contact:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

Vapors may cause drowsiness and dizziness.

SKIN: Rash, Urticaria.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

Water jet (solvent-containing product).

**5.2. Special hazards arising from the substance or mixture**

In case of fire toxic gases can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus.

Wear protective equipment.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Danger of slipping on spilled product.

Keep unprotected persons away.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

**6.3. Methods and material for containment and cleaning up**

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Avoid open flames and sources of ignition.  
Ground/bond container and receiving equipment.  
Use explosion proof electric equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.

## Hygiene measures:

Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.  
Take off contaminated clothing and wash before reuse.

**7.2. Conditions for safe storage, including any incompatibilities**

Ensure good ventilation/extraction.  
Store in a cool, frost-free place.  
Temperatures between + 5 °C and + 25 °C

**7.3. Specific end use(s)**

Contact adhesive

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Cyclohexane 110-82-7 [CYCLOHEXANE]	200	700	Time Weighted Average (TWA):	Indicative	ECLTV
Cyclohexane 110-82-7	200	700	Exposure limit(s):	4	TRGS 900
Cyclohexane 110-82-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethyl acetate 141-78-6 [ETHYL ACETATE]	200	734	Time Weighted Average (TWA):	Indicative	ECLTV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.468	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Ethyl acetate 141-78-6			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Ethyl acetate 141-78-6	200	730	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Magnesium oxide 1309-48-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Magnesium oxide 1309-48-4		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Magnesium oxide 1309-48-4		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Zinc oxide 1314-13-2		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Disulfiram 97-77-8		2	Exposure limit(s):	8	TRGS 900
Disulfiram 97-77-8			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
cyclohexane 110-82-7	aqua (freshwater)		0,207 mg/l				
cyclohexane 110-82-7	aqua (marine water)		0,207 mg/l				
cyclohexane 110-82-7	aqua (intermittent releases)		0,207 mg/l				
cyclohexane 110-82-7	sediment (freshwater)				16,68 mg/kg		
cyclohexane 110-82-7	sediment (marine water)				16,68 mg/kg		
cyclohexane 110-82-7	Soil				3,38 mg/kg		
cyclohexane 110-82-7	sewage treatment plant (STP)		3,24 mg/l				
cyclohexane 110-82-7	Air						
cyclohexane 110-82-7	Predator						no potential for bioaccumulation
Ethyl acetate 141-78-6	aqua (freshwater)		0,24 mg/l				
Ethyl acetate 141-78-6	aqua (marine water)		0,024 mg/l				
Ethyl acetate 141-78-6	aqua (intermittent releases)		1,65 mg/l				
Ethyl acetate 141-78-6	sewage treatment plant (STP)		650 mg/l				
Ethyl acetate 141-78-6	sediment (freshwater)				1,15 mg/kg		
Ethyl acetate 141-78-6	sediment (marine water)				0,115 mg/kg		
Ethyl acetate 141-78-6	Air						no hazard identified
Ethyl acetate 141-78-6	Soil				0,148 mg/kg		
Ethyl acetate 141-78-6	oral				200 mg/kg		
rosin 8050-09-7	aqua (freshwater)		0,002 mg/l				
rosin 8050-09-7	aqua (marine water)		0,0002 mg/l				
rosin 8050-09-7	sediment (freshwater)				0,007 mg/kg		
rosin 8050-09-7	sediment (marine water)				0,001 mg/kg		
rosin 8050-09-7	Soil				0 mg/kg		
rosin 8050-09-7	sewage treatment plant (STP)		1000 mg/l				
rosin 8050-09-7	aqua (intermittent releases)		0,016 mg/l				
zinc oxide 1314-13-2	aqua (freshwater)		14,4 µg/l				
zinc oxide 1314-13-2	aqua (marine water)		7,2 µg/l				
zinc oxide 1314-13-2	sewage treatment plant (STP)		100 µg/l				
zinc oxide 1314-13-2	sediment (freshwater)				146,9 mg/kg		
zinc oxide 1314-13-2	sediment (marine water)				162,2 mg/kg		
zinc oxide 1314-13-2	Soil				83,1 mg/kg		





**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
cyclohexane 110-82-7	Workers	inhalation	Acute/short term exposure - local effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Acute/short term exposure - systemic effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Long term exposure - systemic effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Long term exposure - local effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	dermal	Long term exposure - systemic effects		2016 mg/kg	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Acute/short term exposure - systemic effects		412 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Acute/short term exposure - local effects		412 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	dermal	Long term exposure - systemic effects		1186 mg/kg	no potential for bioaccumulation
cyclohexane 110-82-7	General population	oral	Long term exposure - systemic effects		59,4 mg/kg	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Long term exposure - systemic effects		206 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Long term exposure - local effects		206 mg/m3	no potential for bioaccumulation
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - systemic effects		1468 mg/m3	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - local effects		1468 mg/m3	no hazard identified
Ethyl acetate 141-78-6	Workers	dermal	Long term exposure - systemic effects		63 mg/kg	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - systemic effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - local effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	Inhalation	Acute/short term exposure - systemic effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Acute/short term exposure - local effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	dermal	Long term exposure - systemic effects		37 mg/kg	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - systemic effects		367 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	oral	Long term exposure - systemic effects		4,5 mg/kg	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - local effects		367 mg/m3	no hazard identified
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Workers	dermal	Long term exposure - systemic effects		300 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Workers	inhalation	Long term exposure -		2085 mg/m3	

64742-49-0			systemic effects			
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	dermal	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	inhalation	Long term exposure - systemic effects		447 mg/m3	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	oral	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	Workers	inhalation	Long term exposure - systemic effects		5306 mg/m3	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	Workers	dermal	Long term exposure - systemic effects		13964 mg/kg	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	General population	inhalation	Long term exposure - systemic effects		1131 mg/m3	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	General population	dermal	Long term exposure - systemic effects		1377 mg/kg	
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	General population	oral	Long term exposure - systemic effects		1301 mg/kg	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	dermal	Long term exposure - systemic effects		13964 mg/kg	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	inhalation	Long term exposure - systemic effects		5306 mg/m3	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	dermal	Long term exposure - systemic effects		1377 mg/kg	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	inhalation	Long term exposure - systemic effects		1131 mg/m3	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	oral	Long term exposure - systemic effects		1301 mg/kg	
rosin 8050-09-7	Workers	inhalation	Long term exposure - local effects		10 mg/m3	
rosin 8050-09-7	Workers	dermal	Long term exposure - systemic effects		2,131 mg/kg	
rosin 8050-09-7	General population	dermal	Long term exposure - systemic effects		1,065 mg/kg	
rosin 8050-09-7	General population	oral	Long term exposure - systemic effects		1,065 mg/kg	
zinc oxide 1314-13-2	Workers	Inhalation	Long term exposure - systemic effects		5 mg/m3	
zinc oxide 1314-13-2	Workers	dermal	Long term exposure - systemic effects		83 mg/kg	
zinc oxide 1314-13-2	Workers	inhalation	Long term exposure - local effects		0,5 mg/m3	
zinc oxide 1314-13-2	General population	Inhalation	Long term exposure - systemic effects		2,5 mg/m3	
zinc oxide 1314-13-2	General population	dermal	Long term exposure - systemic effects		83 mg/kg	
zinc oxide 1314-13-2	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	

**Biological Exposure Indices:**

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Cyclohexane 110-82-7	1,2-Cyclohexane diol, with hydrolysis	Creatinine in urine	Sampling time period is for long-term exposures, at the end of the shift after several preceding ones./ Sampling time period is at end of exposure or at end of shift.	150 mg/g	DE BGW		

**8.2. Exposure controls:**

Engineering controls:  
Use only in well ventilated areas.

Respiratory protection:  
In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).  
This recommendation should be matched to local conditions.

Eye protection:  
Goggles which can be tightly sealed.  
Protective eye equipment should conform to EN166.

Skin protection:  
Wear protective equipment.  
Protective clothing that covers arms and legs.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:  
Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.  
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.  
Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	liquid
Delivery form	liquid
Colour	beige
Odor	of solvent
Melting point	Not applicable, Product is a liquid
Solidification temperature	< 5 °C (< 41 °F)
Initial boiling point (1.013 hPa)	70 °C (158 °F)
Flammability	Flammable liquid
Explosive limits lower	0,47 %(V); Upper explosion limit not applicable for safe processing practices.
Flash point	< 0 °C (< 32 °F); DIN 51755 Closed cup flash point
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (40 °C (104 °F); )	3.700 mm <sup>2</sup> /s ;.Dummy
Viscosity, dynamic	3.000 mPa.s Brookfield viscosity (LVT, RVT, HBT)

(Brookfield; Instrument: RVT; 20,0 °C (68 °F); Spindle No: 4)	
Flow cup viscosity (; Nozzle: 6 mm DIN EN ISO 2431; QP2017.1, QP1580.0; Running out time with flow cups)	115 s DIN EN ISO 2431 Running out time with flow cups
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible or difficult to mix
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (55 °C (131 °F))	Mixture 450 mbar
Vapour pressure (20 °C (68 °F))	140 hPa
Vapour pressure (50 °C (122 °F))	510 hPa
Density (20 °C (68 °F))	0,87 g/cm <sup>3</sup> UK-NO. 4/2, density pycnometer
Relative vapour density: (20 °C)	> 1
Particle characteristics	Not applicable Product is a liquid

## 9.2. Other information

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Oxidizers.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

No decomposition if used according to specifications.

## SECTION 11: Toxicological information

### General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
cyclohexane 110-82-7	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Ethyl acetate 141-78-6	LD50	6.100 mg/kg	rat	not specified
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 5.840 mg/kg	rat	not specified
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	LD50	> 16.750 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Formaldehyde, polymer with 4-(1,1- dimethylethyl)phenol 25085-50-1	LD50	> 5.000 mg/kg	rat	not specified
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 16.750 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
rosin 8050-09-7	LD50	2.800 mg/kg	rat	not specified
zinc oxide 1314-13-2	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Disulfiram 97-77-8	LD50	> 1.860 mg/kg	rat	not specified
Disulfiram 97-77-8	Acute toxicity estimate (ATE)	1.861 mg/kg		Expert judgement

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
cyclohexane 110-82-7	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Ethyl acetate 141-78-6	LD50	> 20.000 mg/kg	rabbit	Draize Test
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 2.800 mg/kg	rat	other guideline:
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	LD50	> 3.350 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Formaldehyde, polymer with 4-(1,1- dimethylethyl)phenol 25085-50-1	LD50	> 2.000 mg/kg	rabbit	not specified
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 3.350 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
rosin 8050-09-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
zinc oxide 1314-13-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Disulfiram 97-77-8	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
cyclohexane 110-82-7	LC50	> 32,880 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Ethyl acetate 141-78-6	LC0	> 22,5 mg/l	dust/mist	6 h	rat	other guideline:
Ethyl acetate 141-78-6	LC50	> 22,5 mg/l	dust/mist	6 h	rat	other guideline:
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	LC50	> 23,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	Acute toxicity estimate (ATE)	23,31 mg/l	vapour			Expert judgement
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	LC50	259,354 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LC50	259,354 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
zinc oxide 1314-13-2	LC50	> 5,7 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Disulfiram 97-77-8	LC50	3,464 mg/l	dust/mist	4 h	rat	EPA OPP 81-3 (Acute inhalation toxicity)

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethyl acetate 141-78-6	slightly irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
rosin 8050-09-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
cyclohexane 110-82-7	slightly irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethyl acetate 141-78-6	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	not irritating		rabbit	FDA Guideline
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
rosin 8050-09-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
cyclohexane 110-82-7	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Ethyl acetate 141-78-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
zinc oxide 1314-13-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)



**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
cyclohexane 110-82-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
cyclohexane 110-82-7	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethyl acetate 141-78-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethyl acetate 141-78-6	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
rosin 8050-09-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
zinc oxide 1314-13-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
zinc oxide 1314-13-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
zinc oxide 1314-13-2	ambiguous	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	not carcinogenic	inhalation: vapour	2 years 6 h/d, 5d/week	rat	male/female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
zinc oxide 1314-13-2	not carcinogenic	oral: drinking water	1 y daily	mouse	male/female	not specified

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
cyclohexane 110-82-7	NOAEL F1 7000 ppm	two-generation study	inhalation: vapour	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Ethyl acetate 141-78-6	NOAEL P 1500 ppm	other:	inhalation	rat	other guideline:
zinc oxide 1314-13-2	NOAEL P 7,5 mg/kg NOAEL F1 15 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
cyclohexane 110-82-7		inhalation: vapour	13-14 w 6 h/d, 5 d/w	mouse	EPA OPPTS 870.3465 (90-Day Inhalation Toxicity)
Ethyl acetate 141-78-6	NOAEL 900 mg/kg	oral: gavage	90 d daily	rat	EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
Hydrocarbons, C6, isoalkanes, < 5% n- hexane 64742-49-0	NOAEL 10,504 mg/l	inhalation: vapour	13 weeks 6 h/d, 5 d/week	rat	equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
zinc oxide 1314-13-2	NOAEL 31,52 mg/kg	oral: feed	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
zinc oxide 1314-13-2	NOAEL 1.5 mg/m <sup>3</sup>	inhalation	3 m 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Disulfiram 97-77-8	NOAEL 0,84 mg/kg	oral: feed	52 weeks daily	dog	EPA OPP 83-1 (Chronic Toxicity)

**Aspiration hazard:**

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
cyclohexane 110-82-7	0,41 mm <sup>2</sup> /s	40 °C	not specified	

**11.2 Information on other hazards**

not applicable

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains, soil or bodies of water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
cyclohexane 110-82-7	LC50	4,53 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethyl acetate 141-78-6	LC50	220 mg/l	96 h	Pimephales promelas	other guideline:
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LL50	8,2 mg/l	96 h	Pimephales promelas	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	LL50	18,27 mg/l	96 h	Oncorhynchus mykiss	QSAR (Quantitative Structure Activity Relationship)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	NOELR	4,089 mg/l	28 d	Oncorhynchus mykiss	QSAR (Quantitative Structure Activity Relationship)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	LL50	12 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
rosin 8050-09-7	LC50	Toxicity > Water solubility	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	LC50	0,142 mg/l	96 h	Thymallus arcticus	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	NOEC	0,44 mg/l	72 d	Oncorhynchus mykiss	other guideline:
Disulfiram 97-77-8	NOEC	0,0032 mg/l	10 d	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 210 (fish early lite stage toxicity test)
Disulfiram 97-77-8	LC50	0,067 mg/l	96 h	Lepomis macrochirus	

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
cyclohexane 110-82-7	EC50	0,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethyl acetate 141-78-6	EC50	164 mg/l	48 h	Daphnia cucullata	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EL50	4,5 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	EL50	31,9 mg/l	48 h	Daphnia magna	QSAR (Quantitative Structure Activity Relationship)
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol 25085-50-1	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
rosin 8050-09-7	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
zinc oxide 1314-13-2	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Disulfiram 97-77-8	EC50	0,24 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
-----------------------	------	-----------	------	---------------	--

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	NOEC	2,4 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOELR	2,6 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	NOELR	7,138 mg/l	21 d	Daphnia magna	QSAR (Quantitative Structure Activity Relationship)
zinc oxide 1314-13-2	NOEC	0,058 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
cyclohexane 110-82-7	EC50	9,317 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
cyclohexane 110-82-7	NOEC	0,95 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl acetate 141-78-6	EC50	> 2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl acetate 141-78-6	NOEC	2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EL50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOELR	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	NOELR	3,034 mg/l	72 h	Scenedesmus capricornutum	QSAR (Quantitative Structure Activity Relationship)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	EL50	13,56 mg/l	72 h	Scenedesmus capricornutum	QSAR (Quantitative Structure Activity Relationship)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	EL50	55 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	NOEL	30 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	NOEC	0,017 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	EC50	0,17 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Disulfiram 97-77-8	EC50	1,8 mg/l	96 h	Chlorella pyrenoidosa	OECD Guideline 201 (Alga, Growth Inhibition Test)

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
cyclohexane 110-82-7	IC50	29 mg/l	15 h	other:	not specified
Ethyl acetate 141-78-6	EC10	2.900 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	NOEC	15,81 mg/l	48 h	Ciliate (Tetrahymena pyriformis)	QSAR (Quantitative Structure Activity Relationship)
rosin 8050-09-7	EC20	Toxicity > Water solubility	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
zinc oxide 1314-13-2	IC50	5,2 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

### 12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
cyclohexane 110-82-7	readily biodegradable	aerobic	77 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethyl acetate 141-78-6	readily biodegradable	aerobic	100 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	readily biodegradable	aerobic	77,05 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
rosin 8050-09-7	readily biodegradable	aerobic	71 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Disulfiram 97-77-8		aerobic	20 - 40 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

### 12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
cyclohexane 110-82-7	167			Pimephales promelas	QSAR (Quantitative Structure Activity Relationship)
Ethyl acetate 141-78-6	30	3 d	22,5 °C	Leuciscus idus melanotus	other guideline:
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	501			Pimephales promelas	QSAR (Quantitative Structure Activity Relationship)

### 12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
cyclohexane 110-82-7	3,44	25 °C	QSAR (Quantitative Structure Activity Relationship)
Ethyl acetate 141-78-6	0,68	25 °C	EPA OPPTS 830.7560 (Partition Coefficient, n-octanol / H <sub>2</sub> O, Generator Column Method)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	4,66		EU Method A.8 (Partition Coefficient)
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	3,6	20 °C	not specified
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	3,6	20 °C	other guideline:
rosin 8050-09-7	> 3 - 6,2		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Disulfiram 97-77-8	3,88		not specified

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
cyclohexane 110-82-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethyl acetate 141-78-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C6, isoalkanes, < 5% n-hexane 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
rosin 8050-09-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
zinc oxide 1314-13-2	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code  
080409

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

<b>SECTION 14: Transport information</b>
--

**14.1. UN number or ID number**

ADR	1133
RID	1133
ADN	1133
IMDG	1133
IATA	1133

**14.2. UN proper shipping name**

ADR	ADHESIVES
RID	ADHESIVES
ADN	ADHESIVES
IMDG	ADHESIVES (Cyclohexane)
IATA	Adhesives

**14.3. Transport hazard class(es)**

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

**14.4. Packing group**

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

**14.5. Environmental hazards**

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

**14.6. Special precautions for user**

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

Packed goods < 450 L (ADR/IMDG) can be classified in packaging group III, based of the viscosity (ADR 2.2.3.1.4 und IMDG 2.3.2.2)

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable



**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	71,9 %

**VOC Paints and Varnishes (EU):**

Product (sub)category: This product is not a subject of the Directive 2004/42/EC

**15.2. Chemical safety assessment**

A chemical safety assessment has been carried out.

**National regulations/information (Germany):**

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV) )  
Classification according to AwSV, Annex 1 (5.2)

BG regulations, rules, infos:

BG data sheet: BGI 621 Solvents

Storage class according to TRGS 510: 3

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSInfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**

### Annex - Exposure Scenarios:

Exposure Scenarios for ethyl acetate can be downloaded under the following link:  
<https://mysds.henkel.com/index.html#/appSelection>