

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 24

SDS No.: 453685

V006.0

Revision: 17.01.2024

printing date: 30.01.2024

Replaces version from: 23.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 268 known as LOCTITE 268 19G IT/GR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Threadlocker

1.3. Details of the supplier of the safety data sheet

LOCTITE 268 known as LOCTITE 268 19G IT/GR

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains 3,3,5 Trimethylcyclohexyl methacrylate

Cumene hydroperoxide

Acetic acid, 2-phenylhydrazide

Reaction mass of N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide),

Octadecanamide, 12-hydroxy-N-[2-[(1-oxooctadecyl)amino]ethyl]

Signal word: Warning

Hazard statement: H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement: "***" ***For consumer use only: P101 If medical advice is needed, have product

container or label at hand. P102 Keep out of reach of children. P501 Dispose of

contents/container in accordance with national regulation.***

Precautionary statement: P273 Avoid release to the environment.

Prevention P280 Wear protective gloves.

P261 Avoid breathing vapors.

Precautionary statement: P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Response P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Reaction mass of (1- methylethylidene)bis(4,1- phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4- {2-[2- (methacryloyloxy)ethoxy]ethoxy }phenyl)propan-2- yl]phenoxy}ethyl methacrylate 01-2119980581-32	25- 50 %	Aquatic Chronic 4, H413		
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9 231-927-0 01-2120748527-45	10- 20 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Irrit. 2, H319	STOT SE 3; H335; C >= 10 %	
Reaction mass of N,N'-ethane- 1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy-N- [2-[(1-oxooctadecyl)amino]ethyl] 204-613-6 01-2119978265-26	1-< 5%	Skin Sens. 1, H317		
Cumene hydroperoxide 80-15-9 201-254-7 01-2119475796-19	1- < 3 %	STOT RE 2, H373 Skin Corr. 1B, H314 Acute Tox. 2, Inhalation, H330 Aquatic Chronic 2, H411 Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Org. Perox. E, H242 STOT SE 3, H335	Eye Irrit. 2; H319; C 1 - < 3 % Skin Irrit. 2; H315; C 3 - < 10 % Eye Dam. 1; H318; C 3 - < 10 % STOT SE 3; H335; C >= 1 % Skin Corr. 1B; H314; C >= 10 % ===== dermal:ATE = 1.100 mg/kg	
N,N-Diethyl-p-toluidine 613-48-9 210-345-0	0,1-< 1 %	Acute Tox. 3, Oral, H301 Acute Tox. 3, Dermal, H311 Acute Tox. 3, Inhalation, H331 STOT RE 2, H373 Aquatic Chronic 3, H412 Skin Irrit. 2, H315	dermal:ATE = 300 mg/kg oral:ATE = 100 mg/kg inhalation:ATE = 3 mg/l;vapour	
Acetic acid, 2-phenylhydrazide 114-83-0 204-055-3	0,1-< 1 %	Acute Tox. 3, Oral, H301 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, Inhalation, H335 Carc. 2, H351		
N,N-dimethyl-o-toluidine 609-72-3 210-199-8	0,1-< 1 %	STOT RE 2, H373 Acute Tox. 3, Oral, H301 Acute Tox. 3, Dermal, H311 Acute Tox. 3, Inhalation, H331 Aquatic Chronic 3, H412		
1,4-Naphthalenedione 130-15-4 204-977-6	0,01-< 0,1 %	Acute Tox. 3, Oral, H301 Skin Corr. 1C, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 1, Inhalation, H330 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 10 M chronic = 1	

For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Scrape up as much material as possible.

Sweep up spilled material. Avoid creating dust.

Store in a partly filled, closed container until disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Threadlocker

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list	
Silicon dioxide 112945-52-5		4	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900	
Silicon dioxide 112945-52-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900	
Silicon dioxide 112945-52-5		10	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900	
Silicon dioxide 112945-52-5		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900	
Ethene, homopolymer 9002-88-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900	
Ethene, homopolymer 9002-88-4		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900	
Ethene, homopolymer 9002-88-4		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900	

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
	Compartment	Perrou	mg/l	ppm	mg/kg	others	
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy}phenyl)propan-2-yl]phenoxy}ethyl methacrylate	sewage treatment plant (STP)		1 mg/l	FF			
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	aqua (freshwater)		0,0019 mg/l				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	aqua (marine water)		0,00019 mg/l				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	aqua (intermittent releases)		0,019 mg/l				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sewage treatment plant (STP)		100 mg/l				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sediment (freshwater)				0,141 mg/kg		
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sediment (marine water)				0,014 mg/kg		
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Soil				0,027 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)		0,0031 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)		0,031 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)		0,00031 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sewage treatment plant (STP)		0,35 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Soil				0,0029 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Workers	inhalation	Long term exposure - systemic effects		16,45 mg/m3	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Workers	dermal	Long term exposure - systemic effects		46,7 mg/kg	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	General population	inhalation	Long term exposure - systemic effects		2,9 mg/m3	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	General population	dermal	Long term exposure - systemic effects		1,67 mg/kg	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	General population	oral	Long term exposure - systemic effects		1,67 mg/kg	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	Workers	inhalation	Long term exposure - systemic effects		35,24 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	Workers	inhalation	Acute/short term exposure - systemic effects		35,24 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	Workers	inhalation	Long term exposure - local effects		3,35 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	Workers	inhalation	Acute/short term exposure - local effects		3,35 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	General population	inhalation	Long term exposure - systemic effects		8,69 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	General population	inhalation	Acute/short term exposure - systemic effects		8,69 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	General population	inhalation	Long term exposure - local effects		0,83 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	General population	inhalation	Acute/short term exposure - local effects		0,83 mg/m3	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	General population	oral	Long term exposure - systemic effects		5 mg/kg	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	General population	oral	Acute/short term exposure - systemic effects		5 mg/kg	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Dust mask, P2 particle filter.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form solid
Colour red
Odor Mild, acrylic
Physical state solid

Melting point $> 80 \,^{\circ}\text{C} (> 176 \,^{\circ}\text{F})$

Solidification temperature Not applicable, Product is a solid.

Initial boiling point > 150 °C (> 302 °F) Flammability Not applicable

Non flammable product (flash point is greater than 93°C)

Explosive limits

Not applicable, Product is a solid.

Flash point

Not applicable, Product is a solid.

Auto-ignition temperature

Not applicable, Product is a solid.

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no organic

peroxide and does not decompose under foreseen conditions of use

Not applicable, Product is non-polar/aprotic.

Viscosity (kinematic) Not applicable, Product is a solid.

Solubility (qualitative) Slight

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable Mixture

Vapour pressure < 5,00 mm hg

(26,7 °C (80.1 °F))

Vapour pressure < 0,13 mbar

(20°C (68°F))

pН

Density 1,1 g/cm3 no method / method unknownEstimated

(25 °C (77 °F))

Relative vapour density: Not applicable, Product is a solid.
Particle characteristics Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reducing agents.

Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Hydrocarbons

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy}phenyl)propan-2-yl]phenoxy}ethyl methacrylate	LD50	> 35.000 mg/kg	rat	not specified
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD0	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1- amide), Octadecanamide, 12-hydroxy-N-[2-[(1- oxooctadecyl)amino]ethyl]	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Cumene hydroperoxide 80-15-9	LD50	382 mg/kg	rat	other guideline:
N,N-Diethyl-p-toluidine 613-48-9	Acute toxicity estimate (ATE)	100 mg/kg		Expert judgement
Acetic acid, 2- phenylhydrazide 114-83-0	LD50	270 mg/kg	rat	not specified
1,4-Naphthalenedione 130-15-4	LD50	124 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Reaction mass of (1- methylethylidene)bis(4,1- phenyleneoxy-2,1- ethanediyl) bismethacrylate and 2-{4- [2-(4-{2-[2- (methacryloyloxy)ethoxy] ethoxy}phenyl)propan-2- yl]phenoxy}ethyl methacrylate	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD0	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Cumene hydroperoxide 80-15-9	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
N,N-Diethyl-p-toluidine 613-48-9	Acute toxicity estimate (ATE)	300 mg/kg		Expert judgement

SDS No.: 453685

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	-	Species	Method
CAS-No. Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1- amide), Octadecanamide, 12-hydroxy-N-[2-[(1- oxooctadecyl)amino]ethyl]	LC50	> 5,05 mg/l	dust/mist	time 4 h	rat	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)
Cumene hydroperoxide 80-15-9	LC50	1,370 mg/l	vapour	4 h	rat	not specified
N,N-Diethyl-p-toluidine 613-48-9	Acute toxicity estimate (ATE)	3 mg/l	vapour			Expert judgement
1,4-Naphthalenedione 130-15-4	LC50	0,046 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
			1.1.14	
Reaction mass of (1-	not irritating	24 h	rabbit	not specified
methylethylidene)bis(4,1-				
phenyleneoxy-2,1-				
ethanediyl)				
bismethacrylate and 2-{4-				
[2-(4-{2-[2-				
(methacryloyloxy)ethoxy]				
ethoxy}phenyl)propan-2-				
yl]phenoxy}ethyl				
methacrylate				
Cumene hydroperoxide	corrosive		rabbit	Draize Test
80-15-9				
N,N-Diethyl-p-toluidine	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
613-48-9				
1,4-Naphthalenedione	Category 1C		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
130-15-4	(corrosive)			

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Reaction mass of (1-	not irritating		rabbit	not specified
methylethylidene)bis(4,1-				
phenyleneoxy-2,1-				
ethanediyl)				
bismethacrylate and 2-{4-				
[2-(4-{2-[2-				
(methacryloyloxy)ethoxy]				
ethoxy}phenyl)propan-2-				
yl]phenoxy}ethyl				
methacrylate				

SDS No.: 453685

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
Reaction mass of (1-	not sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
methylethylidene)bis(4,1-		assay (LLNA)		Local Lymph Node Assay)
phenyleneoxy-2,1-				
ethanediyl)				
bismethacrylate and 2-{4-				
[2-(4-{2-[2-				
(methacryloyloxy)ethoxy]				
ethoxy}phenyl)propan-2-				
yl]phenoxy}ethyl				
methacrylate				
3,3,5 Trimethylcyclohexyl	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
methacrylate		assay (LLNA)		Local Lymph Node Assay)
7779-31-9				
Reaction mass of N,N'-	sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
ethane-1,2-diylbis(12-		test		
hydroxyoctadecan-1-				
amide), Octadecanamide,				
12-hydroxy-N-[2-[(1-				
oxooctadecyl)amino]ethyl				
]				
1,4-Naphthalenedione	sensitising	not specified	guinea pig	not specified
130-15-4				

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Reaction mass of (1- methylethylidene)bis(4,1- phenyleneoxy-2,1- ethanediyl) bismethacrylate and 2-{4- [2-(4-{2-[2- (methacryloyloxy)ethoxy] ethoxy}phenyl)propan-2- yl]phenoxy}ethyl methacrylate	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy}phenyl)propan-2-yl]phenoxy}ethyl methacrylate	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Reaction mass of (1- methylethylidene)bis(4,1- phenyleneoxy-2,1- ethanediy1) bismethacrylate and 2-{4- [2-(4-{2-[2- (methacryloyloxy)ethoxy] ethoxy}phenyl)propan-2- yl]phenoxy}ethyl methacrylate	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Reaction mass of (1- methylethylidene)bis(4,1- phenyleneoxy-2,1- ethanediyl) bismethacrylate and 2-{4- [2-(4-{2-[2- (methacryloyloxy)ethoxy] ethoxy}phenyl)propan-2- yl]phenoxy}ethyl methacrylate	NOAEL P 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Reaction mass of (1- methylethylidene)bis(4,1- phenyleneoxy-2,1- ethanediyl) bismethacrylate and 2-{4- [2-(4-{2-[2- (methacryloyloxy)ethoxy] ethoxy}phenyl)propan-2- yl]phenoxy}ethyl methacrylate	NOAEL 1.000 mg/kg	oral: gavage	13 weeks daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	NOAEL 1.000 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SDS No.: 453685

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy}phenyl)propan-2-yl]phenoxy}ethyl methacrylate	LL50	Toxicity > Water solubility	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy]phenyl)propan-2-yl]phenoxy}ethyl methacrylate	NOEC	Toxicity > Water solubility	34 d	Danio rerio	OECD Guideline 210 (fish early lite stage toxicity test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LC50	1,9 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	LL50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	NOELR	Toxicity > Water solubility	32 d	Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
N,N-Diethyl-p-toluidine 613-48-9	LC50	78,62 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
N,N-dimethyl-o-toluidine 609-72-3	LC 50	46 mg/l	96 h	Fathead minnow (Pimephales promelas)	
1,4-Naphthalenedione 130-15-4	LC50	0,045 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Reaction mass of (1-	EL50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202
methylethylidene)bis(4,1-		solubility			(Daphnia sp. Acute
phenyleneoxy-2,1-ethanediyl)		-			Immobilisation Test)

bismethacrylate and 2-{4-[2- (4-{2-[2- (methacryloyloxy)ethoxy]etho xy}phenyl)propan-2- yl]phenoxy}ethyl methacrylate 3,3,5 Trimethylcyclohexyl	EC50	14,43 mg/l	48 h	Daphnia magna	OECD Guideline 202
methacrylate 7779-31-9					(Daphnia sp. Acute Immobilisation Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	EC50	18,84 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	10,34 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-Naphthalenedione 130-15-4	EC50	0,026 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy}phenyl)propan-2-yl]phenoxy}ethyl methacrylate	EC10	Toxicity > Water solubility	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	NOEC	Toxicity > Water solubility	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy]phenyl)propan-2-yl]phenoxy}ethyl methacrylate	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	EC10	0,43 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	EC10	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	EC50	3,1 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	NOEC	1 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	7,42 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	23,69 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	NOEC	0,07 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	EC50	0,42 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy]phenyl)propan-2-yl]phenoxy}ethyl methacrylate	EC50	Toxicity > Water solubility	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	30 min	not specified	not specified
1,4-Naphthalenedione 130-15-4	EC50	5,94 mg/l	3 h	predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

SDS No.: 453685

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy]phenyl)propan-2-yl]phenoxy}ethyl methacrylate	not readily biodegradable.	aerobic	> 19,9 - 41,3 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy]phenyl)propan-2-yl]phenoxy}ethyl methacrylate	inherently biodegradable	aerobic	> 52,2 - 65,5 %	60 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	not readily biodegradable.	aerobic	16,8 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	not readily biodegradable.	aerobic	22 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	not inherently biodegradable	aerobic	37 %	60 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Cumene hydroperoxide 80-15-9	not readily biodegradable.	aerobic	3 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
N,N-Diethyl-p-toluidine 613-48-9	not readily biodegradable.	not specified	1 %	28 day	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
N,N-dimethyl-o-toluidine 609-72-3	not readily biodegradable.		1 %	14 d	other guideline:
1,4-Naphthalenedione 130-15-4	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Cumene hydroperoxide	9,1			calculation	OECD Guideline 305
80-15-9					(Bioconcentration: Flow-through
					Fish Test)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Reaction mass of (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyl) bismethacrylate and 2-{4-[2-(4-{2-[2-(methacryloyloxy)ethoxy]ethoxy}phenyl)propan-2-yl]phenoxy}ethyl methacrylate	> 6,2		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	5,25	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Reaction mass of N,N'- ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide), Octadecanamide, 12-hydroxy- N-[2-[(1- oxooctadecyl)amino]ethyl]	5,86		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Cumene hydroperoxide 80-15-9	1,6	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
N,N-Diethyl-p-toluidine 613-48-9	3,7		QSAR (Quantitative Structure Activity Relationship)
Acetic acid, 2- phenylhydrazide 114-83-0	0,74		not specified
1,4-Naphthalenedione 130-15-4	1,71		not specified

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Reaction mass of (1-methylethylidene)bis(4,1-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
phenyleneoxy-2,1-ethanediyl) bismethacrylate	Bioaccumulative (vPvB) criteria.
and 2-{4-[2-(4-{2-[2-	
(methacryloyloxy)ethoxy]ethoxy}phenyl)propa	
n-2-yl]phenoxy}ethyl methacrylate	
3,3,5 Trimethylcyclohexyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
7779-31-9	Bioaccumulative (vPvB) criteria.
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
1,4-Naphthalenedione	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
130-15-4	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

LOCTITE 268 known as LOCTITE 268 19G IT/GR

SDS No.: 453685

V006.0

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

Not dangerous goods
Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. **Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR not applicable SDS No.: 453685

V006.0

RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content < 3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling

substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 11

SDS No.: 453685

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)

PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.