



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 14

LOCTITE SF 770 Primer (Upgrade)

SDS No. : 677038
V003.1

Revision: 27.04.2023

printing date: 29.04.2023

Replaces version from: 24.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 770 Primer (Upgrade)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Primer

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

ua-productsafety.de@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

isopropyl acetate

Signal word:	Danger
Hazard statement:	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Supplemental information	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statement: Prevention	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapors. P280 Wear protective gloves/protective clothing.
Precautionary statement: Response	P337+P313 If eye irritation persists: Get medical advice/attention.
Precautionary statement: Storage	P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
isopropyl acetate 108-21-4 203-561-1 01-2119537214-46	50- 100 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2 229-713-7 01-2119977097-24	0,1- < 1 %	Acute Tox. 3, Oral, H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Met. Corr. 1, H290	oral:ATE = 215 mg/kg	

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Vapors may cause drowsiness and dizziness.

Prolonged or repeated contact may cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.
See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep away from sources of ignition.
Keep container tightly sealed.
Refer to Technical Data Sheet
Do not store near sources of heat or ignition, or reactive materials.
Store in a cool, well-ventilated place.
Store in a dry place.

7.3. Specific end use(s)

Primer

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
isopropyl acetate 108-21-4	aqua (freshwater)		0,22 mg/l				
isopropyl acetate 108-21-4	aqua (marine water)		0,02 mg/l				
isopropyl acetate 108-21-4	sediment (freshwater)				1,25 mg/kg		
isopropyl acetate 108-21-4	sediment (marine water)				0,125 mg/kg		
isopropyl acetate 108-21-4	Soil				0,35 mg/kg		
isopropyl acetate 108-21-4	sewage treatment plant (STP)		190 mg/l				
isopropyl acetate 108-21-4	aqua (intermittent releases)		1,1 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	aqua (freshwater)		0,24 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	aqua (marine water)		0,024 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	aqua (intermittent releases)		0,5 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	sewage treatment plant (STP)		13 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	sediment (freshwater)				1,46 mg/kg		
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	sediment (marine water)				0,146 mg/kg		
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Soil				0,152 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
isopropyl acetate 108-21-4	Workers	inhalation	Acute/short term exposure - systemic effects		558 mg/m ³	
isopropyl acetate 108-21-4	Workers	inhalation	Long term exposure - local effects		227 mg/m ³	
isopropyl acetate 108-21-4	Workers	inhalation	Long term exposure - systemic effects		275 mg/m ³	
isopropyl acetate 108-21-4	Workers	dermal	Long term exposure - systemic effects		27 mg/kg	
isopropyl acetate 108-21-4	General population	inhalation	Acute/short term exposure - systemic effects		335 mg/m ³	
isopropyl acetate 108-21-4	General population	inhalation	Long term exposure - local effects		136 mg/m ³	
isopropyl acetate 108-21-4	General population	inhalation	Long term exposure - systemic effects		168 mg/m ³	
isopropyl acetate 108-21-4	General population	dermal	Long term exposure - systemic effects		16 mg/kg	
isopropyl acetate 108-21-4	General population	oral	Long term exposure - systemic effects		16 mg/kg	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Workers	inhalation	Long term exposure - systemic effects		10,6 mg/m ³	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Workers	dermal	Long term exposure - systemic effects		3 mg/kg	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	General population	inhalation	Long term exposure - systemic effects		2,6 mg/m ³	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	General population	dermal	Long term exposure - systemic effects		1,5 mg/kg	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	General population	oral	Long term exposure - systemic effects		1,5 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	transparent, Slightly Hazy
Odor	aromatic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Initial boiling point	82 °C (179.6 °F)
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	4 °C (39.2 °F); Tagliabue closed cup
Auto-ignition temperature	Currently under determination
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	Currently under determination
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (50 °C (122 °F))	Mixture < 700 mbar
Vapour pressure (20 °C (68 °F))	56 mbar
Density ()	0,87 g/cm ³ no method / method unknown
Relative vapour density:	Currently under determination
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used properly.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

None if used properly.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
isopropyl acetate 108-21-4	LD50	6.750 mg/kg	rat	other guideline:
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Acute toxicity estimate (ATE)	215 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
isopropyl acetate 108-21-4	LD50	> 17.400 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
isopropyl acetate 108-21-4	LC50	50,6 mg/l	vapour	8 h	rat	not specified

Skin corrosion/irritation:

No data available.

Serious eye damage/irritation:

No data available.

Respiratory or skin sensitization:

No data available.

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
isopropyl acetate 108-21-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure:

No data available.

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
isopropyl acetate 108-21-4	LC50	400 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	LC50	> 100 - 220 mg/l	96 h	Leuciscus idus	DIN 38412-15

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
isopropyl acetate 108-21-4	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	EC50	50 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	NOEC	> 12 mg/l	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	EC50	> 100 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	NOEC	> 100 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	EC 50	330 mg/l	17 h		not specified

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
isopropyl acetate 108-21-4	readily biodegradable	aerobic	72 %	20 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	not inherently biodegradable	aerobic	< 20 %	28 day	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	not readily biodegradable.	aerobic	< 20 %	28 day	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	< 0,4	42 day		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
isopropyl acetate 108-21-4	1,28		not specified

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
isopropyl acetate 108-21-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1220
RID	1220
ADN	1220
IMDG	1220
IATA	1220

14.2. UN proper shipping name

ADR	ISOPROPYL ACETATE
RID	ISOPROPYL ACETATE
ADN	ISOPROPYL ACETATE
IMDG	ISOPROPYL ACETATE
IATA	Isopropyl acetate

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	99,9 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 3

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.