



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 15

LOCTITE SF 770

SDS No. : 153555
V004.2

Revision: 01.03.2023
printing date: 06.03.2023

Replaces version from: 18.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 770

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Primer

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Aspiration hazard	Category 1
H304 May be fatal if swallowed and enters airways.	
Acute hazards to the aquatic environment	Category 1
H400 Very toxic to aquatic life.	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

n-Heptane

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement:

"***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing vapors.
 P273 Avoid release to the environment.

**Precautionary statement:
Response**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P331 Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
n-Heptane 142-82-5 205-563-8 01-2119457603-38	50- 100 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	EU OEL
Methylcyclohexane 108-87-2 203-624-3	0,1- < 1 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2 229-713-7 01-2119977097-24	0,1- < 1 %	Acute Tox. 3, Oral, H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Met. Corr. 1, H290	oral:ATE = 215 mg/kg	

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

After ingestion or vomit: danger of product entering the lung.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema

Vapors may cause drowsiness and dizziness.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Do not induce vomiting.

Seek medical attention from a specialist.

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.
Do not expose to direct heat.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.
Avoid contact with skin and eyes.
Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.
See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Store in a cool, dry place.
Do not store near sources of heat or ignition, or reactive materials.
Refer to Technical Data Sheet

7.3. Specific end use(s)

Primer

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Heptane 142-82-5 [N-HEPTANE]	500	2.085	Time Weighted Average (TWA):	Indicative	ECLTV
Heptane 142-82-5	500	2.100	Exposure limit(s):	1	TRGS 900
Heptane 142-82-5			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Heptane 142-82-5		1.500	Exposure limit(s):	2	TRGS 900
Heptane 142-82-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Methylcyclohexane 108-87-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Methylcyclohexane 108-87-2	200	810	Exposure limit(s):	2	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
n-Heptane 142-82-5	Air						no hazard identified
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	aqua (freshwater)		0,24 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	aqua (marine water)		0,024 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	aqua (intermittent releases)		0,5 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	sewage treatment plant (STP)		13 mg/l				
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	sediment (freshwater)				1,46 mg/kg		
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	sediment (marine water)				0,146 mg/kg		
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Soil				0,152 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
n-Heptane 142-82-5	Workers	dermal	Long term exposure - systemic effects		300 mg/kg	no hazard identified
n-Heptane 142-82-5	Workers	Inhalation	Long term exposure - systemic effects		2085 mg/m ³	no hazard identified
n-Heptane 142-82-5	General population	dermal	Long term exposure - systemic effects		149 mg/kg	no hazard identified
n-Heptane 142-82-5	General population	Inhalation	Long term exposure - systemic effects		447 mg/m ³	no hazard identified
n-Heptane 142-82-5	General population	oral	Long term exposure - systemic effects		149 mg/kg	no hazard identified
Methylcyclohexane 108-87-2	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Methylcyclohexane 108-87-2	Workers	Inhalation	Long term exposure - systemic effects		2035 mg/m ³	
Methylcyclohexane 108-87-2	General population	dermal	Long term exposure - systemic effects		699 mg/kg	
Methylcyclohexane 108-87-2	General population	Inhalation	Long term exposure - systemic effects		608 mg/m ³	
Methylcyclohexane 108-87-2	General population	oral	Long term exposure - systemic effects		699 mg/kg	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Workers	inhalation	Long term exposure - systemic effects		10,6 mg/m ³	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Workers	dermal	Long term exposure - systemic effects		3 mg/kg	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	General population	inhalation	Long term exposure - systemic effects		2,6 mg/m ³	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	General population	dermal	Long term exposure - systemic effects		1,5 mg/kg	
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	General population	oral	Long term exposure - systemic effects		1,5 mg/kg	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Heptane 142-82-5 [n-Heptane]	Heptan-2,5-dione	Urine	Sampling time: End of shift.	250 µg/l	DE BGW		

8.2. Exposure controls:

Engineering controls:

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Delivery form	liquid
Colour	clear, colourless
Odor	Of hydrocarbons
Melting point	Not applicable, Product is a liquid
Solidification temperature	-75 °C (-103 °F)
Initial boiling point	98 °C (208.4 °F)None
Flammability	Flammable liquid
Explosive limits	
lower	1,1 %(V);
upper	6,7 %(V);
	Upper/lower explosion limit
Flash point	-4 °C (24.8 °F)
Auto-ignition temperature	223 °C (433.4 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (25 °C (77 °F);)	0,6 mm2/s
Viscosity (kinematic) (40 °C (104 °F);)	<= 20,5 mm2/s
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible
Partition coefficient: n-octanol/water	Not applicable

Vapour pressure (20 °C (68 °F))	Mixture 5,33 kPa
Density (20 °C (68 °F))	0,68 g/cm ³ None
Relative vapour density: (20 °C)	3,4 (Air = 1)
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity
10.1. Reactivity

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information
11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
n-Heptane 142-82-5	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Methylcyclohexane 108-87-2	LD50	> 3.200 mg/kg	rat	not specified
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Acute toxicity estimate (ATE)	215 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
n-Heptane 142-82-5	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Methylcyclohexane 108-87-2	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
n-Heptane 142-82-5	LC50	> 29,29 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Methylcyclohexane 108-87-2	LC50	> 26,3 mg/l	vapour	1 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
n-Heptane 142-82-5	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Methylcyclohexane 108-87-2	not irritating	24 h	rabbit	Draize Test

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
n-Heptane 142-82-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Methylcyclohexane 108-87-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
n-Heptane 142-82-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Methylcyclohexane 108-87-2	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
n-Heptane 142-82-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-Heptane 142-82-5	negative	in vitro mammalian chromosome aberration test	not applicable		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Methylcyclohexane 108-87-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Methylcyclohexane 108-87-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Methylcyclohexane 108-87-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
n-Heptane 142-82-5	NOAEL P 3000 ppm NOAEL F1 3000 ppm		inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Methylcyclohexane 108-87-2	NOAEL P 250 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
n-Heptane 142-82-5		inhalation: vapour	16 weeks 12 hours/day, 7 days/week	rat	
Methylcyclohexane 108-87-2	NOAEL 250 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
n-Heptane 142-82-5	LC50	> 220 - 270 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methylcyclohexane 108-87-2	LC50	2,07 mg/l	96 h	Oryzias latipes	other guideline:
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	LC50	> 100 - 220 mg/l	96 h	Leuciscus idus	DIN 38412-15

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
n-Heptane 142-82-5	EC50	1,5 mg/l	48 h	Daphnia magna	other guideline:
Methylcyclohexane 108-87-2	EC50	0,326 mg/l	48 h	Daphnia magna	other guideline:
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	EC50	50 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
n-Heptane 142-82-5	NOELR	1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	NOEC	> 12 mg/l	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methylcyclohexane 108-87-2	EC50	0,134 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	other guideline:
Methylcyclohexane 108-87-2	NOEC	0,022 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	other guideline:
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	EC50	> 100 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	NOEC	> 100 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	EC 50	330 mg/l	17 h		not specified

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
n-Heptane 142-82-5	readily biodegradable	aerobic	70 %	10 d	other guideline:
Methylcyclohexane 108-87-2	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	not inherently biodegradable	aerobic	< 20 %	28 day	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	not readily biodegradable.	aerobic	< 20 %	28 day	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
n-Heptane 142-82-5	552			calculation	QSAR (Quantitative Structure Activity Relationship)
Methylcyclohexane 108-87-2	> 95 - < 321	56 day	25 °C	Cyprinus carpio	other guideline:
1,8-Diazabicyclo[5.4.0]undec- 7-ene 6674-22-2	< 0,4	42 day		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
n-Heptane 142-82-5	4,66		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Methylcyclohexane 108-87-2	3,88		other guideline:

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
n-Heptane 142-82-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,8-Diazabicyclo[5.4.0]undec-7-ene 6674-22-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1206
RID	1206
ADN	1206
IMDG	1206
IATA	1206

14.2. UN proper shipping name

ADR	HEPTANES (solution)
RID	HEPTANES (solution)
ADN	HEPTANES (solution)
IMDG	HEPTANES (n-Heptane) (solution)
IATA	Heptanes (solution)

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 3

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.
H301 Toxic if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSInfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.