



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 24

LOCTITE PC 7226 1KG EN/DE

SDS No. : 178249

V001.0

Revision: 05.09.2019

printing date: 04.04.2021

Replaces version from: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE PC 7226 1KG EN/DE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy Hardener

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Acute toxicity	Category 3
H331 Toxic if inhaled.	
Route of Exposure: Inhalation	
Skin corrosion	Sub-category 1B
H314 Causes severe skin burns and eye damage.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Toxic to reproduction	Category 1B
H360F May damage fertility.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Diethylenetriamine

C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer

4,4'-Isopropylidenediphenol

Fatty acids, tall-oil, reaction products with tetraethylenepentamine

Triethylenetetramine

N-(3-(Trimethoxysilyl)propyl)ethylenediamine

3,6,9-Triazaundecamethylenediamine

Signal word:

Danger

Hazard statement:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Supplemental information

Restricted to professional users.

**Precautionary statement:
Prevention**

P201 Obtain special instructions before use.

P260 Do not breathe dusts or mists.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement:
Response**

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

P308+P313 IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

Part B of a two part adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Diethylenetriamine 111-40-0	203-865-4 01-2119473793-27	10- 20 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Corr. 1B H314 Skin Sens. 1 H317 Acute Tox. 2; Inhalation H330 STOT SE 3 H335 Eye Dam. 1 H318
4,4'-Isopropylidenediphenol 80-05-7	201-245-8 01-2119457856-23	3- < 10 %	Aquatic Chronic 2 H411 Eye Dam. 1 H318 Skin Sens. 1 H317 STOT SE 3 H335 Repr. 1B H360F ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC) EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC) EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	500-191-5 01-2119972320-44	3- < 10 %	Skin Irrit. 2 H315 Eye Dam. 1 H318 Skin Sens. 1A H317 Aquatic Chronic 2 H411
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	273-201-6	3- < 10 %	Skin Irrit. 2 H315 Eye Dam. 1 H318 Skin Sens. 1 H317 Aquatic Chronic 1 H410 Aquatic Acute 1 H400
Manganese dioxide 1313-13-9	215-202-6	1- < 5 %	Acute Tox. 4; Inhalation H332 Acute Tox. 4; Oral H302 STOT RE 2; Inhalation H373
Triethylenetetramine 112-24-3	203-950-6 01-2119487919-13	0,1- < 1 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Sens. 1 H317 Skin Corr. 1B H314 Aquatic Chronic 3 H412
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	217-164-6 01-2119970215-39	0,1- < 1 %	Skin Sens. 1 H317 Eye Dam. 1 H318

			Acute Tox. 4; Inhalation H332 STOT RE 2; Inhalation H373
3,6,9-Triazaundecamethylenediamine 112-57-2	203-986-2 01-2119487290-37	0,1- < 1 %	Acute Tox. 4; Dermal H312 Acute Tox. 4; Oral H302 Skin Sens. 1 H317 Aquatic Chronic 2 H411 Skin Corr. 1B H314

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.
Avoid contact with skin and eyes.
Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.
See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container.
Protect against contamination.
Refer to Technical Data Sheet

7.3. Specific end use(s)

Epoxy Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Aluminium oxide 1344-28-1		10	Exposure limit(s):	2	TRGS 900
Aluminium oxide 1344-28-1		1,25	Exposure limit(s):		TRGS 900
Silicon carbide 409-21-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Silicon carbide 409-21-2		10	Exposure limit(s):	2	TRGS 900
Silicon carbide 409-21-2		1,25	Exposure limit(s):		TRGS 900
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE FRACTION)]		2	Time Weighted Average (TWA):	Indicative	ECTLV
4,4'-Isopropylidenediphenol 80-05-7			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
4,4'-Isopropylidenediphenol 80-05-7		5	Exposure limit(s):	1 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Linear low density polyethylene 9002-88-4		1,25	Exposure limit(s):		TRGS 900
Linear low density polyethylene 9002-88-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Linear low density polyethylene 9002-88-4		10	Exposure limit(s):	2	TRGS 900
Manganese dioxide 1313-13-9		0,2	Exposure limit(s):	8 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Manganese dioxide 1313-13-9			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Manganese dioxide 1313-13-9		0,02	Exposure limit(s):	8 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Manganese dioxide 1313-13-9			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Manganese dioxide 1313-13-9 [MANGANESE AND INORGANIC MANGANESE COMPOUNDS (AS MN) (RESPIRABLE FRACTION)]		0,05	Time Weighted Average (TWA):	Indicative	ECTLV
Manganese dioxide 1313-13-9 [MANGANESE AND INORGANIC MANGANESE COMPOUNDS (AS MN) (INHALABLE FRACTION)]		0,2	Time Weighted Average (TWA):	Indicative	ECTLV

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2,2'-Iminodi(ethylamine) 111-40-0	aqua (freshwater)		0,56 mg/l				
2,2'-Iminodi(ethylamine) 111-40-0	aqua (marine water)		0,056 mg/l				
2,2'-Iminodi(ethylamine) 111-40-0	aqua (intermittent releases)		0,32 mg/l				
2,2'-Iminodi(ethylamine) 111-40-0	sediment (freshwater)				1072 mg/kg		
2,2'-Iminodi(ethylamine) 111-40-0	sediment (marine water)				107,2 mg/kg		
2,2'-Iminodi(ethylamine) 111-40-0	sewage treatment plant (STP)		6 mg/l				
2,2'-Iminodi(ethylamine) 111-40-0	Soil				7,97 mg/kg		
2,2'-Iminodi(ethylamine) 111-40-0	Air						
4,4'-Isopropylidenediphenol 80-05-7	aqua (freshwater)		0,018 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (marine water)		0,018 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (intermittent releases)		0,011 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sewage treatment plant (STP)		320 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sediment (freshwater)				1,2 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	sediment (marine water)				0,24 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Soil				3,7 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Air						
4,4'-Isopropylidenediphenol 80-05-7	Predator						
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	aqua (freshwater)		0,00434 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	aqua (marine water)		0,00043 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	aqua (intermittent releases)		0,0434 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sewage treatment plant (STP)		3,84 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sediment (freshwater)				434,02 mg/kg		
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sediment (marine water)				43,4 mg/kg		
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Soil				86,78 mg/kg		
Trientine 112-24-3	aqua (intermittent releases)		0,2 mg/l				
Trientine 112-24-3	aqua (freshwater)		0,027 mg/l				
Trientine 112-24-3	aqua (marine water)		0,003 mg/l				
Trientine 112-24-3	Sewage treatment plant		0,13 mg/l				
Trientine	sediment				8,572		

112-24-3	(freshwater)				mg/kg		
Trientine	sediment				0,857		
112-24-3	(marine water)				mg/kg		
Trientine	Soil				1,25 mg/kg		
112-24-3							
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	aqua (freshwater)		0,062 mg/l				
1760-24-3							
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	aqua (marine water)		0,0062 mg/l				
1760-24-3							
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	aqua (intermittent releases)		0,62 mg/l				
1760-24-3							
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	sediment (freshwater)				0,22 mg/kg		
1760-24-3							
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	sediment (marine water)				0,022 mg/kg		
1760-24-3							
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Soil				0,0085 mg/kg		
1760-24-3							
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	sewage treatment plant (STP)		25 mg/l				
1760-24-3							
3,6,9-Triazaundecamethylenediamine	Soil				0,683 mg/kg		
112-57-2							
3,6,9-Triazaundecamethylenediamine	aqua (freshwater)		0,0068 mg/l				
112-57-2							
3,6,9-Triazaundecamethylenediamine	aqua (marine water)		0,00068 mg/l				
112-57-2							
3,6,9-Triazaundecamethylenediamine	sediment (freshwater)				3,43 mg/kg		
112-57-2							
3,6,9-Triazaundecamethylenediamine	sediment (marine water)				0,343 mg/kg		
112-57-2							
3,6,9-Triazaundecamethylenediamine	sewage treatment plant (STP)		9,73 mg/l				
112-57-2							

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-Iminodi(ethylamine) 111-40-0	Workers	dermal	Long term exposure - systemic effects		11,4 mg/kg	
2,2'-Iminodi(ethylamine) 111-40-0	Workers	dermal	Long term exposure - local effects		1,1 mg/kg	
2,2'-Iminodi(ethylamine) 111-40-0	Workers	Inhalation	Acute/short term exposure - systemic effects		92,1 mg/m3	
2,2'-Iminodi(ethylamine) 111-40-0	Workers	Inhalation	Acute/short term exposure - local effects		2,6 mg/m3	
2,2'-Iminodi(ethylamine) 111-40-0	Workers	Inhalation	Long term exposure - systemic effects		15,4 mg/m3	
2,2'-Iminodi(ethylamine) 111-40-0	Workers	Inhalation	Long term exposure - local effects		0,87 mg/m3	
2,2'-Iminodi(ethylamine) 111-40-0	General population	dermal	Acute/short term exposure - systemic effects		4,88 mg/kg	
2,2'-Iminodi(ethylamine) 111-40-0	General population	Inhalation	Acute/short term exposure - systemic effects		27,5 mg/m3	
2,2'-Iminodi(ethylamine) 111-40-0	General population	dermal	Long term exposure - systemic effects		4,88 mg/kg	
2,2'-Iminodi(ethylamine) 111-40-0	General population	Inhalation	Long term exposure - systemic effects		4,6 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Acute/short term exposure - systemic effects		0,031 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Long term exposure - systemic effects		0,031 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Acute/short term exposure - systemic effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Long term exposure - systemic effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Long term exposure - systemic effects		0,002 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	General population	Inhalation	Long term exposure - systemic effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Long term exposure - local effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Acute/short term exposure - local effects		2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - systemic effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Long term exposure - local effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - local effects		1 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Acute/short term exposure - systemic effects		0,002 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Long term exposure - systemic effects		0,004 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Acute/short term exposure -		0,004 mg/kg	

			systemic effects			
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Workers	inhalation	Long term exposure - systemic effects		3,9 mg/m3	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Workers	dermal	Long term exposure - systemic effects		1,1 mg/kg	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	General population	inhalation	Long term exposure - systemic effects		0,97 mg/m3	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	General population	dermal	Long term exposure - systemic effects		0,56 mg/kg	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	General population	oral	Long term exposure - systemic effects		0,56 mg/kg	
Trientine 112-24-3	Workers	inhalation	Long term exposure - systemic effects		0,54 mg/m3	
Trientine 112-24-3	General population	inhalation	Long term exposure - systemic effects		0,096 mg/m3	
Trientine 112-24-3	General population	oral	Long term exposure - systemic effects		0,14 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	inhalation	Long term exposure - systemic effects		35,3 mg/m3	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Long term exposure - systemic effects		5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Acute/short term exposure - systemic effects		5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Long term exposure - systemic effects		8,7 mg/m3	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	dermal	Acute/short term exposure - systemic effects		17 mg/kg	
3,6,9-Triazaundecamethylenediamine 112-57-2	Workers	dermal	Long term exposure - systemic effects		0,74 mg/kg	
3,6,9-Triazaundecamethylenediamine 112-57-2	Workers	inhalation	Long term exposure - systemic effects		1,29 mg/m3	
3,6,9-Triazaundecamethylenediamine 112-57-2	Workers	inhalation	Acute/short term exposure - systemic effects		6940 mg/m3	
3,6,9-Triazaundecamethylenediamine 112-57-2	General population	dermal	Long term exposure - systemic effects		0,32 mg/kg	
3,6,9-Triazaundecamethylenediamine 112-57-2	General population	inhalation	Long term exposure - systemic effects		0,38 mg/m3	
3,6,9-Triazaundecamethylenediamine 112-57-2	General population	oral	Long term exposure - systemic effects		0,53 mg/kg	
3,6,9-Triazaundecamethylenediamine 112-57-2	General population	oral	Acute/short term exposure - systemic effects		26 mg/kg	
3,6,9-Triazaundecamethylenediamine 112-57-2	General population	inhalation	Acute/short term exposure - systemic effects		2071 mg/m3	
3,6,9-Triazaundecamethylenediamine 112-57-2	General population	dermal	Acute/short term exposure - systemic effects		10 mg/kg	
3,6,9-Triazaundecamethylenediamine 112-57-2	General population	dermal	Acute/short term exposure - local effects		1,29 mg/cm2	

3,6,9-Triazaundecamethylenediamine 112-57-2	General population	dermal	Long term exposure - local effects		0,56 mg/cm2	
3,6,9-Triazaundecamethylenediamine 112-57-2	Workers	dermal	Long term exposure - local effects		0,036 mg/cm2	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Aluminium oxide 1344-28-1	Aluminum	Urine	Sampling time: End of shift.	200 µg/l	DE BAT		
Manganese dioxide 1313-13-9	Manganese	Blood	Sampling time: End of shift at end of work week.	20 µg/l	DE BAT		

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

paste
paste, solid
black

Odor

characteristic

Odour threshold

No data available / Not applicable

pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 200 °C (> 392 °F)
Flash point	> 100 °C (> 212 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure (50 °C (122 °F))	< 700 mbar
Relative vapour density:	No data available / Not applicable
Density (g/cm ³)	2,2311 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	practically insoluble
Solubility (qualitative) (Solvent: Acetone)	Partially soluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.

Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diethylenetriamine 111-40-0	LD50	1.553 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- Isopropylidenediphenol 80-05-7	LD50	> 2.000 - < 5.000 mg/kg		
4,4'- Isopropylidenediphenol 80-05-7	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	LD50	> 4.750 mg/kg	rat	not specified
Triethylenetetramine 112-24-3	LD50	1.591 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LD50	2.295 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)
3,6,9- Triazaundecamethylenedi amine 112-57-2	LD50	1.716 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diethylenetriamine 111-40-0	LD50	1.045 mg/kg	rabbit	not specified
4,4'- Isopropylidenediphenol 80-05-7	LD50	3.600 mg/kg	rabbit	not specified
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	LD50	> 2.000 mg/kg		not specified
Triethylenetetramine 112-24-3	LD50	1.465 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LD50	> 2.000 mg/kg	rat	EPA OPPTS 870.1200 (Acute Dermal Toxicity)
3,6,9- Triazaundecamethylenedi amine 112-57-2	LD50	1.260 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Diethylenetriamine 111-40-0	NOEL	0,07 mg/l			rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Diethylenetriamine 111-40-0	Acute toxicity estimate (ATE)	0,07 mg/l	dust/mist			Expert judgement
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	LC50	1,49 - 2,44 mg/l	dust/mist	4 h	rat	EPA OPPTS 870.1300 (Acute inhalation toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diethylenetriamine 111-40-0	corrosive	15 min	rabbit	BASF Test
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	irritating		In vitro	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	irritating			Weight of evidence
Triethylenetetramine 112-24-3	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
3,6,9-Triazaundecamethylenediamine 112-57-2	corrosive	4 h	rabbit	Draize Test

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diethylenetriamine 111-40-0	corrosive	30 s	rabbit	not specified
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	Category I			Weight of evidence
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Diethylenetriamine 111-40-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
4,4'- Isopropylidenediphenol 80-05-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 406 (Skin Sensitisation)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	sensitising			Weight of evidence
Triethylenetetramine 112-24-3	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	sensitising	Mouse local lymphnode assay (LLNA)	guinea pig	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
3,6,9- Triazaundecamethylenedi amine 112-57-2	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Diethylenetriamine 111-40-0	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Diethylenetriamine 111-40-0	negative	in vitro mammalian chromosome aberration test	with and without		Chromosome Aberration Test
4,4'- Isopropylidenediphenol 80-05-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Triethylenetetramine 112-24-3	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Triethylenetetramine 112-24-3	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
3,6,9- Triazaundecamethylenedi amine 112-57-2	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
3,6,9- Triazaundecamethylenedi amine 112-57-2	ambiguous	sister chromatid exchange assay in mammalian cells	with and without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
3,6,9- Triazaundecamethylenedi amine 112-57-2	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Diethylenetriamine 111-40-0	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Diethylenetriamine 111-40-0	negative	oral: gavage		mouse	not specified
Triethylenetetramine 112-24-3	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
3,6,9- Triazaundecamethylenedi amine 112-57-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Diethylenetriamine 111-40-0	not carcinogenic	dermal	lifetime (appr. 587 d) 3 d/w	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Diethylenetriamine 111-40-0	NOAEL P 100 mg/kg NOAEL F1 30 mg/kg	screening	oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
4,4'- Isopropylidenediphenol 80-05-7	NOAEL P 300 ppm		oral: feed	mouse	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Diethylenetriamine 111-40-0	NOAEL 70 - 80 mg/kg	oral: feed	90 d daily	rat	not specified
Diethylenetriamine 111-40-0	NOAEL 0,55 mg/l	inhalation: vapour	15 d 6 h/d	rat	not specified
Triethylenetetramine 112-24-3	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Triethylenetetramine 112-24-3	NOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,6,9- Triazaundecamethylenedi amine 112-57-2	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,6,9- Triazaundecamethylenedi amine 112-57-2	NOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	LC50	430 mg/l	96 h	Poecilia reticulata	EU Method C.1 (Acute Toxicity for Fish)
Diethylenetriamine 111-40-0	NOEC	> 10 mg/l	28 d	Gasterosteus aculeatus	OECD Guideline 210 (fish early life stage toxicity test)
4,4'-Isopropylidenediphenol 80-05-7	LC50	4,6 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol 80-05-7	NOEC	0,016 mg/l	444 d	Pimephales promelas	EPA OPP 72-5 (Fish Life Cycle Toxicity)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	LC50	7,07 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	LC50	0,19 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Manganese dioxide 1313-13-9	LC50		96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Triethylenetetramine 112-24-3	LC50	570 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	LC50	168 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,6,9-Triazaundecamethylenediamine 112-57-2	LC50	420 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	EC50	64,6 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
4,4'-Isopropylidenediphenol 80-05-7	EC50	3,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	EC50	1,48 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Manganese dioxide 1313-13-9	EC50		48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Triethylenetetramine 112-24-3	EC50	31 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	EC50	87,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,6,9-Triazaundecamethylenediamine 112-57-2	EC50	24,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

112-57-2					
----------	--	--	--	--	--

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	NOEC	5,6 mg/l	21 d	Daphnia magna	EU Method C.20 (Daphnia magna Reproduction Test)
4,4'-Isopropylidenediphenol 80-05-7	NOEC	0,17 mg/l	28 d	Americamysis bahia	EPA OPPTS 850.1350 (Mysid Chronic Toxicity Test)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	NOEC	0,32 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	NOEC	> 1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	EC50	1.164 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diethylenetriamine 111-40-0	NOEC	10 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC50	> 2,73 - 3,1 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	1,36 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	EC50	4,34 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	EC50	0,638 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	EC10	0,395 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Manganese dioxide 1313-13-9	EC50		72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Manganese dioxide 1313-13-9	NOEC		72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triethylenetetramine 112-24-3	EC10	< 2,5 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triethylenetetramine 112-24-3	EC50	20 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3-(Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC50	8,8 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3-(Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	NOEC	3,1 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6,9- Triazaundecamethylenediamin e 112-57-2	NOEC	0,5 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6,9- Triazaundecamethylenediamin e 112-57-2	EC50	6,8 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	NOEC	6 mg/l	3 h	anaerobic bacteria	not specified
4,4'-Isopropylidenediphenol 80-05-7	EC10	> 320 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	EC10	130 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	EC10	24 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

68953-36-6					
Manganese dioxide 1313-13-9	EC50		3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Triethylenetetramine 112-24-3	EC0	137 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	EC 50	435 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
3,6,9-Triazaundecamethylenediamine 112-57-2	EC 50	1.600 mg/l	1 h		EU Method C.11 (Biodegradation: Activated Sludge Respiration Inhibition Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Diethylenetriamine 111-40-0	inherently biodegradable	aerobic	83 %	28 d	EU Method C.9 (Biodegradation: Zahn-Wellens Test)
Diethylenetriamine 111-40-0	readily biodegradable	aerobic	87 %	21 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
4,4'-Isopropylidenediphenol 80-05-7	readily biodegradable	aerobic	89 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	not readily biodegradable.	no data	0 - 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	not readily biodegradable.	aerobic	24 %	28 day	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Triethylenetetramine 112-24-3	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Triethylenetetramine 112-24-3	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3		aerobic	50 %		OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
3,6,9-Triazaundecamethylenediamine 112-57-2	under test conditions no biodegradation observed	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Diethylenetriamine 111-40-0	> 0,3 - < 6,3	42 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
4,4'-Isopropylidenediphenol 80-05-7	5,1 - 67	42 d	25 °C	Cyprinus carpio	other guideline:

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Diethylenetriamine 111-40-0	-1,58	20 °C	QSAR (Quantitative Structure Activity Relationship)
4,4'-Isopropylidenediphenol 80-05-7	3,4	21,5 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	10,34		QSAR (Quantitative Structure Activity Relationship)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	2,2	25,2 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-Stirring Method)
Triethylenetetramine 112-24-3	-2,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-1,67		not specified
3,6,9-Triazaundecamethylenediamine 112-57-2	-3,16		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Diethylenetriamine 111-40-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4,4'-Isopropylidenediphenol 80-05-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Fatty acids, tall-oil, reaction products with tetraethylenepentamine 68953-36-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Triethylenetetramine 112-24-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3,6,9-Triazaundecamethylenediamine 112-57-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Collection and delivery to recycling enterprise or other registered elimination institution.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	1759
RID	1759
ADN	1759
IMDG	1759
IATA	1759

14.2. UN proper shipping name

ADR	CORROSIVE SOLID, N.O.S. (Diethylenetriamine,Triethylenetetramine)
RID	CORROSIVE SOLID, N.O.S. (Diethylenetriamine)
ADN	CORROSIVE SOLID, N.O.S. (Diethylenetriamine,Triethylenetetramine)
IMDG	CORROSIVE SOLID, N.O.S. (Diethylenetriamine,Triethylenetetramine,Fatty acids, tall-oil, reaction products with tetraethylenepentamine)
IATA	Corrosive solid, n.o.s. (Diethylenetriamine,Triethylenetetramine)

14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC)	10,2 %
-----------------------------	--------

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK:	WGK = 3, highly water endangering mixture. Classification according to the mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April 2017.
Storage class according to TRGS 510:	6.1C
General remarks (DE):	This product is in scope of the German regulation "Chemikalien Verbots Verordnung"

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H360F May damage fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 16

LOCTITE PC 7226 1KG EN/DE

SDS No. : 152835

V001.0

Revision: 05.09.2019

printing date: 04.04.2021

Replaces version from: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE PC 7226 1KG EN/DE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy resin

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)

Bisphenol-F epichlorhydrin resin; MW<700
Oxirane, [[(2-ethylhexyl)oxy]methyl]-

Signal word:	Warning
Hazard statement:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement:	P273 Avoid release to the environment.
Prevention	P280 Wear protective gloves.
Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Part A of two part adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	01-2119456619-26	10- 20 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Aquatic Chronic 2 H411
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	01-2119454392-40	10- 20 %	Skin Irrit. 2; Dermal H315 Skin Sens. 1A H317 Aquatic Chronic 2 H411
Oxirane, [[(2-ethylhexyl)oxy]methyl]- 2461-15-6	219-553-6 01-2119962196-31	1- < 5 %	Skin Sens. 1 H317

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Sulphur oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

See advice in section 8

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Hygiene measures:

- Wash hands before work breaks and after finishing work.
- Do not eat, drink or smoke while working.
- Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

- Store only in the original container.
- Protect against contamination.
- Store in a cool, well-ventilated place.
- Refer to Technical Data Sheet

7.3. Specific end use(s)

Epoxy resin

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Aluminium oxide 1344-28-1		10	Exposure limit(s):	2	TRGS 900
Aluminium oxide 1344-28-1		1,25	Exposure limit(s):		TRGS 900
Silicon carbide 409-21-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Silicon carbide 409-21-2		10	Exposure limit(s):	2	TRGS 900
Silicon carbide 409-21-2		1,25	Exposure limit(s):		TRGS 900
Silicon dioxide 7631-86-9		4	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Magnesium oxide 1309-48-4		10	Exposure limit(s):	2	TRGS 900
Magnesium oxide 1309-48-4		1,25	Exposure limit(s):		TRGS 900
Magnesium oxide 1309-48-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	aqua (freshwater)		0,006 mg/l				
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	aqua (marine water)		0,001 mg/l				
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	sewage treatment plant (STP)		10 mg/l				
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	sediment (freshwater)				0,996 mg/kg		
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	sediment (marine water)				0,1 mg/kg		
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Soil				0,196 mg/kg		
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	oral				11 mg/kg		
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	aqua (intermittent releases)		0,018 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (freshwater)		0,003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (marine water)		0,0003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sewage treatment plant (STP)		10 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sediment (freshwater)				0,294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sediment (marine water)				0,0294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Soil				0,237 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (intermittent releases)		0,0254 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Air						
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Predator						

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	dermal	Acute/short term exposure - systemic effects		8,33 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	Inhalation	Acute/short term exposure - systemic effects		12,25 mg/m3	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	dermal	Long term exposure - systemic effects		8,33 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	Inhalation	Long term exposure - systemic effects		12,25 mg/m3	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	General population	dermal	Acute/short term exposure - systemic effects		3,571 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	General population	dermal	Long term exposure - systemic effects		3,571 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	General population	oral	Acute/short term exposure - systemic effects		0,75 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	General population	oral	Long term exposure - systemic effects		0,75 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	General population	inhalation	Acute/short term exposure - systemic effects		0,75 mg/m3	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	General population	inhalation	Long term exposure - systemic effects		0,75 mg/m3	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	dermal	Long term exposure - systemic effects		104,15 mg/kg	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m3	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	dermal	Long term exposure - systemic effects		62,5 mg/kg	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m3	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	dermal	Acute/short term exposure - local effects		8,3 µg/cm2	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Aluminium oxide 1344-28-1	Aluminum	Urine	Sampling time: End of shift.	200 µg/l	DE BAT		

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste paste, solid grey
Odor	mild
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 200 °C (> 392 °F)
Flash point	> 100 °C (> 212 °F); None
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable

Explosive limits	No data available / Not applicable
Vapour pressure (50 °C (122 °F))	< 700 mbar
Relative vapour density:	No data available / Not applicable
Density (g/cm ³)	2,3337 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Not miscible
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reaction with strong acids.

Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Irritating organic vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Oxirane, [[(2- ethylhexyl)oxy]methyl]- 2461-15-6	LD50	7.800 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Oxirane, [[(2- ethylhexyl)oxy]methyl]- 2461-15-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	moderately irritating	24 h	rabbit	Draize Test
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	NOAEL P > 750 mg/kg NOAEL F1 750 mg/kg NOAEL F2 750 mg/kg	two- generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	LC50	5,7 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	EC50	2,55 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	EC50	1,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Oxirane, [[(2-ethylhexyl)oxy]methyl]- 2461-15-6	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available for the product.

No substance data available.

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	3,242	25 °C	EU Method A.8 (Partition Coefficient)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	2,7 - 3,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Oxirane, [[(2-ethylhexyl)oxy]methyl]- 2461-15-6	3,83		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Oxirane, [[(2-ethylhexyl)oxy]methyl]- 2461-15-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3,00 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK = 2, water endangering product. Classification according to the mixture rules in German VwVwS regulation annex 4 from 27.July 2005.

WGK: WGK = 2, significantly water endangering mixture. Classification according to the mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April 2017.

Storage class according to TRGS 510: 11

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.