

TEROSON SB 2140

October 2018

PRODUCT DESCRIPTION

TEROSON SB 2140 provides the following product characteristics:

Technology	Polychloroprene
Product Type	Solventbased adhesive
Application	Assembly
Appearance	beige

TEROSON SB 2140 is a solvent containing contact adhesive based on polychloroprene.

TEROSON SB 2140 has excellent initial adhesion and the ability to bond varying substrates to one another.

TEROSON SB 2140 is particularly used when the bondings have to withstand temperatures (up to 120°C).

TEROSON SB 2140 is adjusted for spray application.

Application Areas:

TEROSON SB 2140 can be used as a general purpose adhesive to bond various materials like wood, variable plastics, metals, felts, and many more, to themselves and to one another.

TEROSON SB 2140 can not be used for bonding of polystyrene foam, PE, PP, PTFE and soft PVC.

TECHNICAL DATA

Colour:	beige
Odour:	of solvents
Density:	approx. 0.83 g/cm ³
Solids, %	16.5
Viscosity (ISO 2555-89); mPa.s:	~200
Epprecht Spindle 2, 20°C	
Diluent / Cleaner:	TEROSON VR 50, TEROSON VR 40
Consumption, g/m ² :	150 to 250 g/cm ²
Flash-off time, min:	15 to 20 min.
Application temperature, °C:	18 to 25
In service temperature range, °C:	-30 to 120
Short exposure (up to 1 h):	130 °C

DIRECTIONS OF USE

Preliminary Statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Pre-Treatment:

The bonding surfaces must be dry and free of oil, grease, dust and anti-adhesive constituents. Rubber parts must be free of talcum and other gliding agents.

Application:

Stir TEROSON SB 2140 before use. The adhesive is then applied uniformly to both bonding surfaces with a brush or spatula (smooth or fine notched).

Depending on application method, layer thickness, temperature, room ventilation and humidity the parts coated with adhesive must be allowed an open time of approx. 15 to 20 minutes. (The so-called "finger test" has proven itself a more reliable judgement of the open time than the time data. The adhesive must be dry but slightly tacky). Taking exact care of the open time is important, for the bonding results can be influenced by a too short as well as too long waiting period.

Match the Parts exactly and press them quickly but firmly.

Cleaning:

Adhesive residues/stains can be removed before curing - including application equipment and containers - with Teroson VR 40 or Teroson VR 50 (precheck compatibility with the substrates).

Classification:

Please refer to the corresponding **Material Safety Data Sheets** for details on:

Hazards identification
Transport information
Regulatory information

Storage:

Recommended storage temperature, °C 10 to 20
Shelf-life (in unopened original packaging), 12 months

ADDITIONAL INFORMATION**Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.0