



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 19

TEROSON RB II GY

SDS No. : 75672
V007.2

Revision: 12.09.2023

printing date: 18.09.2023

Replaces version from: 02.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON RB II GY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

1-Component sealant

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

SDSinfo.Adhesive@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable solids

Category 1

H228 Flammable solid.

Skin irritation

Category 2

H315 Causes skin irritation.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Danger

| | |
|--|--|
| Hazard statement: | H228 Flammable solid. H315 Causes skin irritation. H411 Toxic to aquatic life with long lasting effects. |
| Precautionary statement: Prevention | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273 Avoid release to the environment. P280 Wear protective gloves. |
| Precautionary statement: Response | P370+P378 In case of fire: Use CO ₂ , dry chemical, or foam for extinction. |
| Precautionary statement: Storage | P403+P235 Store in a well-ventilated place. Keep cool. |

2.3. Other hazards

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|--|---------------|---|---|------------------|
| Naphtha (petroleum), hydrotreated light ----- 921-024-6 01-2119475514-35 | 10- < 17,5 % | Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 | | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 276-737-9 01-2119474878-16 | 1- < 3 % | Asp. Tox. 1, H304 | | |
| cyclohexane 110-82-7 203-806-2 01-2119463273-41 | 0,25- < 2,5 % | Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Flam. Liq. 2, H225 Skin Irrit. 2, H315 | M acute = 1 M chronic = 1 | EU OEL |
| n-Hexane 110-54-3 203-777-6 01-2119480412-44 | 0,1- < 1 % | Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 | STOT RE 2; H373; C \geq 5 % | EU OEL |

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid open flames and sources of ignition.
Ground/bond container and receiving equipment.
Use explosion proof electric equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.

Hygiene measures:

Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.
Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Store in a cool, dry place.
Storage at 15 to 20°C is recommended.

7.3. Specific end use(s)

1-Component sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-------------------------------------|--|-----------------|
| Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 | | | Short Term Exposure Classification: | Category II: substances with a resorptive effect. | TRGS 900 |
| Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 | | 10 | Exposure limit(s): | 2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 | | 1,25 | Exposure limit(s): | If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| Limestone 1317-65-3 | | | Short Term Exposure Classification: | Category II: substances with a resorptive effect. | TRGS 900 |
| Limestone 1317-65-3 | | 1,25 | Exposure limit(s): | If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| Limestone 1317-65-3 | | 10 | Exposure limit(s): | 2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| Cyclohexane 110-82-7 [CYCLOHEXANE] | 200 | 700 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Cyclohexane 110-82-7 | 200 | 700 | Exposure limit(s): | 4 | TRGS 900 |
| Cyclohexane 110-82-7 | | | Short Term Exposure Classification: | Category II: substances with a resorptive effect. | TRGS 900 |
| Dolomite 16389-88-1 | | | Short Term Exposure Classification: | Category II: substances with a resorptive effect. | TRGS 900 |
| Dolomite 16389-88-1 | | 10 | Exposure limit(s): | 2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| Dolomite 16389-88-1 | | 1,25 | Exposure limit(s): | If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| n-Hexane 110-54-3 [N-HEXANE] | 20 | 72 | Time Weighted Average (TWA): | Indicative | ECLTV |
| n-Hexane 110-54-3 | 50 | 180 | Exposure limit(s): | 8 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7). | TRGS 900 |
| n-Hexane 110-54-3 | | | Short Term Exposure Classification: | Category II: substances with a resorptive effect. | TRGS 900 |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------------|-----------------|------------|-----|----------------|--------|-------------------------------------|
| | | | mg/l | ppm | mg/kg | others | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | oral | | | | 9,33 mg/kg | | |
| cyclohexane 110-82-7 | aqua (freshwater) | | 0,207 mg/l | | | | |
| cyclohexane 110-82-7 | aqua (marine water) | | 0,207 mg/l | | | | |
| cyclohexane 110-82-7 | aqua (intermittent releases) | | 0,207 mg/l | | | | |
| cyclohexane 110-82-7 | sediment (freshwater) | | | | 16,68 mg/kg | | |
| cyclohexane 110-82-7 | sediment (marine water) | | | | 16,68 mg/kg | | |
| cyclohexane 110-82-7 | Soil | | | | 3,38 mg/kg | | |
| cyclohexane 110-82-7 | sewage treatment plant (STP) | | 3,24 mg/l | | | | |
| cyclohexane 110-82-7 | Air | | | | | | |
| cyclohexane 110-82-7 | Predator | | | | | | no potential for bioaccumulation |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|--|---------------|------------------------|----------------------------------|
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ----- | Workers | inhalation | Long term exposure - systemic effects | | 2035 mg/m ³ | |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ----- | Workers | dermal | Long term exposure - systemic effects | | 773 mg/kg | |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ----- | General population | inhalation | Long term exposure - systemic effects | | 608 mg/m ³ | |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ----- | General population | dermal | Long term exposure - systemic effects | | 699 mg/kg | |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ----- | General population | oral | Long term exposure - systemic effects | | 699 mg/kg | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | Workers | inhalation | Long term exposure - systemic effects | | 2,73 mg/m ³ | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | Workers | inhalation | Long term exposure - local effects | | 5,58 mg/m ³ | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | Workers | dermal | Long term exposure - systemic effects | | 0,97 mg/kg | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | General population | oral | Long term exposure - systemic effects | | 0,74 mg/kg | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | General population | inhalation | Long term exposure - local effects | | 1,19 mg/m ³ | |
| cyclohexane 110-82-7 | Workers | inhalation | Acute/short term exposure - local effects | | 700 mg/m ³ | no potential for bioaccumulation |
| cyclohexane 110-82-7 | Workers | inhalation | Acute/short term exposure - systemic effects | | 700 mg/m ³ | no potential for bioaccumulation |
| cyclohexane 110-82-7 | Workers | inhalation | Long term exposure - systemic effects | | 700 mg/m ³ | no potential for bioaccumulation |
| cyclohexane 110-82-7 | Workers | inhalation | Long term exposure - local effects | | 700 mg/m ³ | no potential for bioaccumulation |
| cyclohexane 110-82-7 | Workers | dermal | Long term exposure - systemic effects | | 2016 mg/kg | no potential for bioaccumulation |
| cyclohexane 110-82-7 | General population | inhalation | Acute/short term exposure - systemic effects | | 412 mg/m ³ | no potential for bioaccumulation |
| cyclohexane 110-82-7 | General population | inhalation | Acute/short term exposure - local effects | | 412 mg/m ³ | no potential for bioaccumulation |
| cyclohexane 110-82-7 | General population | dermal | Long term exposure - systemic effects | | 1186 mg/kg | no potential for bioaccumulation |
| cyclohexane 110-82-7 | General population | oral | Long term exposure - systemic effects | | 59,4 mg/kg | no potential for bioaccumulation |
| cyclohexane 110-82-7 | General population | inhalation | Long term exposure - systemic effects | | 206 mg/m ³ | no potential for bioaccumulation |
| cyclohexane 110-82-7 | General population | inhalation | Long term exposure - local effects | | 206 mg/m ³ | no potential for bioaccumulation |
| n-Hexane 110-54-3 | General population | inhalation | Long term exposure - systemic effects | | 16 mg/m ³ | |

| | | | | | | |
|----------------------|--------------------|------------|---------------------------------------|--|----------------------|--|
| n-Hexane 110-54-3 | Workers | dermal | Long term exposure - systemic effects | | 11 mg/kg | |
| n-Hexane 110-54-3 | General population | dermal | Long term exposure - systemic effects | | 5,3 mg/kg | |
| n-Hexane 110-54-3 | Workers | inhalation | Long term exposure - systemic effects | | 75 mg/m ³ | |
| n-Hexane 110-54-3 | General population | oral | Long term exposure - systemic effects | | 4 mg/kg | |

Biological Exposure Indices:

| Ingredient [Regulated substance] | Parameters | Biological specimen | Sampling time | Conc. | Basis of biol. exposure index | Remark | Additional Information |
|----------------------------------|--|---------------------|--|----------|-------------------------------|--------|------------------------|
| Cyclohexane 110-82-7 | 1,2-Cyclohexane diol, with hydrolysis | Creatinine in urine | Sampling time period is for long-term exposures, at the end of the shift after several preceding ones./ Sampling time period is at end of exposure or at end of shift. | 150 mg/g | DE BGW | | |
| n-Hexane 110-54-3 | Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone | Urine | Sampling time: End of shift. | 5 mg/l | DE BAT | | |
| n-Hexane 110-54-3 | Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone (with hydrolysis) | Urine | Sampling time: End of shift. | 5 mg/l | DE BGW | | |

8.2. Exposure controls:**Engineering controls:**

Ensure good ventilation/extraction.

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction.

If intensive ventilation/extraction is not possible respiratory protection equipment with ABEK P2 filter (EN 14387) should be worn.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| Delivery form | paste |
| Colour | dark grey |
| Odor | of solvent |
| Physical state | solid |
| Melting point | Not applicable, Determination technically not possible |
| Solidification temperature | Not applicable, Product is a solid. |
| Initial boiling point (1.013 hPa) | 80 °C (176 °F)Supplier's method |
| Flammability | flammable |
| Explosive limits | Not applicable, Product is a solid. |
| Flash point | -9 °C (15.8 °F); DIN 51755 Closed cup flash point |
| Auto-ignition temperature | Not applicable, Product is a solid. |
| Decomposition temperature | Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use |
| pH | Not applicable, Product is non-soluble (in water). |
| Viscosity (kinematic) | Not applicable, Product is a solid. |
| Viscosity, dynamic () | Not available. |
| Solubility (qualitative) (20 °C (68 °F); Solvent: Water) | Insoluble |
| Partition coefficient: n-octanol/water | Not applicable |
| Vapour pressure (20 °C (68 °F)) | Mixture < 1 hPa |
| Density (20 °C (68 °F)) | 1,40 g/cm ³ QP2107.1; Density |
| Relative vapour density: | Not applicable, Product is a solid. |
| Particle characteristics | Not applicable, mixture is a paste. |

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

| | |
|------------------|----------------------------------|
| Flammable Solids | |
| Burning rate | 6,67 mm/s |
| Burning time | 15 s; no method / method unknown |

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information**General toxicological information:**

An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|---------------|---------------|---------|---|
| Naphtha (petroleum), hydrotreated light ----- | LD50 | > 5.840 mg/kg | rat | not specified |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based, <3 % DMSO extract 72623-86-0 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| cyclohexane 110-82-7 | LD50 | > 5.000 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| n-Hexane 110-54-3 | LD50 | 16.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|---------------|---------------|---------|---|
| Naphtha (petroleum), hydrotreated light ----- | LD50 | > 2.800 mg/kg | rat | not specified |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based, <3 % DMSO extract 72623-86-0 | LD50 | > 5.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| cyclohexane 110-82-7 | LD50 | > 2.000 mg/kg | rabbit | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| n-Hexane 110-54-3 | LD50 | > 2.000 mg/kg | rabbit | not specified |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---|------------|---------------|-----------------|---------------|---------|---|
| Naphtha (petroleum), hydrotreated light ----- | LC50 | > 25,2 mg/l | vapour | 4 h | rat | not specified |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | LC50 | > 5,53 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| cyclohexane 110-82-7 | LC50 | > 32,880 mg/l | vapour | 4 h | rat | equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) |
| n-Hexane 110-54-3 | LC50 | > 31,86 mg/l | vapour | 4 h | rat | not specified |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------|---------------|---------|---|
| Naphtha (petroleum), hydrotreated light ----- | irritating | 4 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| n-Hexane 110-54-3 | not irritating | | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|---------------------|---------------|---------|--|
| cyclohexane 110-82-7 | slightly irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| n-Hexane 110-54-3 | not irritating | | rabbit | not specified |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|------------------------------|-----------------|------------------------------------|------------|--|
| cyclohexane 110-82-7 | not sensitising | Buehler test | guinea pig | equivalent or similar to OECD Guideline 406 (Skin Sensitisation) |
| n-Hexane 110-54-3 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|------------------------------|----------|--|--------------------------------------|---------|--|
| cyclohexane 110-82-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| cyclohexane 110-82-7 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| n-Hexane 110-54-3 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| n-Hexane 110-54-3 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| cyclohexane 110-82-7 | negative | inhalation: vapour | | rat | equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| n-Hexane 110-54-3 | negative | inhalation: vapour | | mouse | not specified |
| n-Hexane 110-54-3 | negative | inhalation: vapour | | rat | not specified |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|------------------------------|------------------|----------------------|--|---------|--------|--|
| n-Hexane 110-54-3 | not carcinogenic | inhalation: vapour | 2 y 6 h/d; 5 d/w | mouse | female | OECD Guideline 451 (Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|------------------------------|--|----------------------|----------------------|---------|--|
| cyclohexane 110-82-7 | NOAEL F1 7000 ppm | two-generation study | inhalation: vapour | rat | equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |
| n-Hexane 110-54-3 | NOAEL P 9000 ppm NOAEL F1 3000 ppm NOAEL F2 3000 ppm | Two generation study | inhalation: vapour | rat | OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---------------------------------|-----------------|-------------------------|--|---------|---|
| cyclohexane 110-82-7 | | inhalation: vapour | 13-14 w 6 h/d, 5 d/w | mouse | EPA OPPTS 870.3465 (90-Day Inhalation Toxicity) |
| n-Hexane 110-54-3 | NOAEL 568 mg/kg | oral: gavage | 90 d 5 d/w | rat | not specified |
| n-Hexane 110-54-3 | NOAEL 500 ppm | inhalation: vapour | 90 d 6 h/d; 5 d/w | mouse | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |

Aspiration hazard:

The mixture is classified based on Viscosity data.

| Hazardous substances CAS-No. | Viscosity (kinematic) Value | Temperature | Method | Remarks |
|---|--------------------------------|-------------|---------------|---------|
| Naphtha (petroleum), hydrotreated light ----- | 0,61 mm ² /s | 25 °C | not specified | |
| cyclohexane 110-82-7 | 0,41 mm ² /s | 40 °C | not specified | |
| n-Hexane 110-54-3 | 0,45 mm ² /s | 25 °C | not specified | |

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|------------|---------------|---------------|---------------------|--|
| Naphtha (petroleum), hydrotreated light ----- | LL50 | 11,4 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | LL50 | > 100 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| cyclohexane 110-82-7 | LC50 | 4,53 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| n-Hexane 110-54-3 | LC50 | > 1 - 10 mg/l | 96 h | not specified | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|------------|---------------|---------------|---------------|--|
| Naphtha (petroleum), hydrotreated light ----- | EL50 | 3 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | EL50 | > 10.000 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| cyclohexane 110-82-7 | EC50 | 0,9 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| n-Hexane 110-54-3 | EC50 | 2,1 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|------------|-----------|---------------|---------------|---|
| Naphtha (petroleum), hydrotreated light ----- | NOEC | 0,17 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | NOELR | 10 mg/l | 21 day | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|------------|-----------------|---------------|--|---|
| Naphtha (petroleum), hydrotreated light ----- | EL50 | > 30 - 100 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Naphtha (petroleum), hydrotreated light ----- | NOELR | 3 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | NOELR | > 100 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| cyclohexane 110-82-7 | EC50 | 9,317 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| cyclohexane 110-82-7 | NOEC | 0,95 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| n-Hexane 110-54-3 | EC50 | > 1 - 10 mg/l | 72 h | not specified | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|------------------------------|------------|---------------|---------------|---------------|--|
| cyclohexane 110-82-7 | IC50 | 29 mg/l | 15 h | other: | not specified |
| n-Hexane 110-54-3 | EC50 | > 1 - 10 mg/l | 3 h | not specified | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|----------------------------|-----------|---------------|---------------|---|
| Naphtha (petroleum), hydrotreated light ----- | readily biodegradable | aerobic | 98 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | not readily biodegradable. | aerobic | 31 % | 28 day | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| cyclohexane 110-82-7 | readily biodegradable | aerobic | 77 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| n-Hexane 110-54-3 | readily biodegradable | aerobic | 81 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|------------------------------|-------------------------------|---------------|-------------|---------------------|---|
| cyclohexane 110-82-7 | 167 | | | Pimephales promelas | QSAR (Quantitative Structure Activity Relationship) |

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---------------------------------|--------|-------------|---|
| cyclohexane 110-82-7 | 3,44 | 25 °C | QSAR (Quantitative Structure Activity Relationship) |
| n-Hexane 110-54-3 | 4 | 20 °C | other guideline: |

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Naphtha (petroleum), hydrotreated light ----- | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, <3 % DMSO extract 72623-86-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| cyclohexane 110-82-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| n-Hexane 110-54-3 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

080409

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

| | |
|------|------|
| ADR | 3175 |
| RID | 3175 |
| ADN | 3175 |
| IMDG | 3175 |
| IATA | 3175 |

14.2. UN proper shipping name

| | |
|------|--|
| ADR | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Solvent naphtha) |
| RID | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Solvent naphtha) |
| ADN | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Solvent naphtha) |
| IMDG | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Solvent naphtha,Cyclohexane) |
| IATA | Solids containing flammable liquid, n.o.s. (Solvent naphtha) |

14.3. Transport hazard class(es)

| | |
|------|-----|
| ADR | 4.1 |
| RID | 4.1 |
| ADN | 4.1 |
| IMDG | 4.1 |
| IATA | 4.1 |

14.4. Packing group

| | |
|------|----|
| ADR | II |
| RID | II |
| ADN | II |
| IMDG | II |
| IATA | II |

14.5. Environmental hazards

| | |
|------|---------------------------|
| ADR | Environmentally Hazardous |
| RID | Environmentally Hazardous |
| ADN | Environmentally Hazardous |
| IMDG | Marine Pollutant |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|-----------------------------------|
| ADR | not applicable Tunnelcode: (E) |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |
| VOC content (2010/75/EU) | 17,1 % |

VOC Paints and Varnishes (EU):

Product (sub)category: This product is not a subject of the Directive 2004/42/EC

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

BG regulations, rules, infos:

BG data sheet: BGI 621 Solvents

Storage class according to TRGS 510: 4.1B

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties
EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2: Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

