



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

TEROSON VR 190

SDS No. : 76482
V010.0

Revision: 01.02.2024

printing date: 12.02.2024

Replaces version from: 27.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON VR 190

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Car-care product

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Aspiration hazard	Category 1
H304 May be fatal if swallowed and enters airways.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Propan-2-ol

Signal word:**Danger****Hazard statement:**

H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P273 Avoid release to the environment.
 P261 Avoid breathing vapors.
 P280 Wear protective gloves/eye protection.

**Precautionary statement:
Response**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
 P331 Do NOT induce vomiting.
 P370+P378 In case of fire: Use CO₂, dry chemical, or foam for extinction.

**Precautionary statement:
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ----- 921-024-6 01-2119475514-35	60- 80 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411		
Propan-2-ol 67-63-0 200-661-7 01-2119457558-25	20- 40 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
n-Hexane 110-54-3 203-777-6 01-2119480412-44	0,25- < 2,5 %	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	STOT RE 2; H373; C >= 5 %	EU OEL

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

Declaration of ingredients according to Detergent Regulation 648/2004/EC

> 30 % aliphatic hydrocarbons

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

After ingestion or vomit: danger of product entering the lung.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Do not induce vomiting.

Seek medical attention from a specialist.

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

Water jet (solvent-containing product).

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid open flames and sources of ignition.

Ground/bond container and receiving equipment.

Use explosion proof electric equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
 Storage at 5 to 25°C is recommended.
 Store in a cool place.
 Keep container tightly sealed.
 Keep container in a well ventilated place.

7.3. Specific end use(s)

Car-care product

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Propan-2-ol 67-63-0			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Propan-2-ol 67-63-0	200	500	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):	Indicative	ECTLV
n-Hexane 110-54-3	50	180	Exposure limit(s):	8 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Hexane 110-54-3			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Propan-2-ol 67-63-0	aqua (freshwater)		140,9 mg/l				
Propan-2-ol 67-63-0	aqua (marine water)		140,9 mg/l				
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	Soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)		140,9 mg/l				
Propan-2-ol 67-63-0	sewage treatment plant (STP)		2251 mg/l				
Propan-2-ol 67-63-0	oral				160 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	Workers	inhalation	Long term exposure - systemic effects		2035 mg/m ³	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	General population	inhalation	Long term exposure - systemic effects		608 mg/m ³	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	General population	dermal	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	General population	oral	Long term exposure - systemic effects		699 mg/kg	
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure - systemic effects		500 mg/m ³	
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m ³	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	
n-Hexane 110-54-3	General population	inhalation	Long term exposure - systemic effects		16 mg/m ³	
n-Hexane 110-54-3	Workers	dermal	Long term exposure - systemic effects		11 mg/kg	
n-Hexane 110-54-3	General population	dermal	Long term exposure - systemic effects		5,3 mg/kg	
n-Hexane 110-54-3	Workers	inhalation	Long term exposure - systemic effects		75 mg/m ³	
n-Hexane 110-54-3	General population	oral	Long term exposure - systemic effects		4 mg/kg	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Propan-2-ol 67-63-0	acetone	Blood	Sampling time: End of shift.	25 mg/l	DE BGW		
Propan-2-ol 67-63-0 [2-PROPANOL]	acetone	Urine	Sampling time: End of shift.	25 mg/l	DE BGW		
n-Hexane 110-54-3	Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone	Urine	Sampling time: End of shift.	5 mg/l	DE BAT		
n-Hexane 110-54-3	Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone (with hydrolysis)	Urine	Sampling time: End of shift.	5 mg/l	DE BGW		

8.2. Exposure controls:

Engineering controls:

Use only in well ventilated areas.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; ≥ 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; ≥ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	colourless
Odor	of solvent
Physical state	liquid

Melting point	Not applicable, Product is a liquid
Solidification temperature	< -50 °C (< -58 °F)
Initial boiling point (1.013 hPa)	80 °C (176 °F)Supplier method
Flammability	Flammable liquid
Explosive limits lower	1,47 % (V); Upper explosion limit not applicable for safe processing practices.
Flash point	3 °C (37.4 °F); Supplier method
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (40 °C (104 °F);)	1,24 mm ² /s ;Supplier method
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture 9400 Pa
Vapour pressure (50 °C (122 °F))	36000 Pa
Density (20 °C (68 °F))	0,72 g/cm ³ Supplier method
Relative vapour density: (20 °C)	1,13
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Oxidizers.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	LD50	> 5.840 mg/kg	rat	not specified
Propan-2-ol 67-63-0	LD50	5.840 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
n-Hexane 110-54-3	LD50	16.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	LD50	> 2.800 mg/kg	rat	not specified
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
n-Hexane 110-54-3	LD50	> 2.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	LC50	> 25,2 mg/l	vapour	4 h	rat	not specified
n-Hexane 110-54-3	LC50	> 31,86 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
n-Hexane 110-54-3	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Propan-2-ol 67-63-0	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
n-Hexane 110-54-3	not irritating		rabbit	not specified

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
n-Hexane 110-54-3	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
n-Hexane 110-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-Hexane 110-54-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
n-Hexane 110-54-3	negative	inhalation: vapour		mouse	not specified
n-Hexane 110-54-3	negative	inhalation: vapour		rat	not specified

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
n-Hexane 110-54-3	not carcinogenic	inhalation: vapour	2 y 6 h/d; 5 d/w	mouse	female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Propan-2-ol 67-63-0	NOAEL P 853 mg/kg	One generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 500 mg/kg NOAEL F1 1.000 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
n-Hexane 110-54-3	NOAEL P 9000 ppm NOAEL F1 3000 ppm NOAEL F2 3000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	Category 3 with narcotic effects.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
n-Hexane 110-54-3	NOAEL 568 mg/kg	oral: gavage	90 d 5 d/w	rat	not specified
n-Hexane 110-54-3	NOAEL 500 ppm	inhalation: vapour	90 d 6 h/d; 5 d/w	mouse	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	0,61 mm ² /s	25 °C	not specified	
Propan-2-ol 67-63-0	1,8 mm ² /s	40 °C	ASTM Standard D7042	
n-Hexane 110-54-3	0,45 mm ² /s	25 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	LL50	11,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
n-Hexane 110-54-3	LC50	> 1 - 10 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
n-Hexane 110-54-3	EC50	2,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Propan-2-ol 67-63-0	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	EL50	> 30 - 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	NOELR	3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
n-Hexane 110-54-3	readily biodegradable	aerobic	81 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Propan-2-ol 67-63-0	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
n-Hexane 110-54-3	4	20 °C	other guideline:

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propan-2-ol 67-63-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
n-Hexane 110-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1993
RID	1993
ADN	1993
IMDG	1993
IATA	1993

14.2. UN proper shipping name

ADR	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Isopropanol)
RID	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Isopropanol)
ADN	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Isopropanol)
IMDG	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Isopropanol)
IATA	Flammable liquid, n.o.s. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Isopropanol)

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	100 %

VOC Paints and Varnishes (EU):

Product (sub)category: This product is not a subject of the Directive 2004/42/EC

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

BG regulations, rules, infos:

BG data sheet: BGI 621 Solvents

Storage class according to TRGS 510: 3

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.