

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

## LOCTITE SI 5300 RD

SDS No. : 656973 V006.1 Revision: 25.05.2023 printing date: 29.05.2023 Replaces version from: 12.12.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1. Product identifier** LOCTITE SI 5300 RD
- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Silicone adhesive

## 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA Henkelstr. 67 40589 Düsseldorf

Germany

Phone: +49 211 797 0

## SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification (CLP):	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	

### 2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Warning

Hazard statement:	H315 Causes skin irritation. H319 Causes serious eye irritation.
Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response	P337+P313 If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

None if used properly.

Self-classification according to Article 12(b) of (EU) 1272/2008.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

octamethylcyclotetrasiloxane PBT/vPvB 556-67-2

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Triacetoxyethylsilane 17689-77-9 241-677-4 01-2119881778-15	1-< 3%	Eye Dam. 1, H318 Acute Tox. 4, Oral, H302 Skin Corr. 1B, H314		
octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36	0,01-< 0,1 %	Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226	M chronic = 10	SVHC PBT/vPvB

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed** SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

**Suitable extinguishing media:** water, carbon dioxide, foam, powder

### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released. Silicon dioxide

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

### Additional information:

In case of fire, keep containers cool with water spray.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective equipment. Ensure adequate ventilation.

### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13. For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Keep container tightly sealed. Refer to Technical Data Sheet

**7.3. Specific end use(s)** Silicone adhesive

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

## **Occupational Exposure Limits**

## Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9		4	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Diiron trioxide 1309-37-1			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Diiron trioxide 1309-37-1		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Diiron trioxide 1309-37-1		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

# Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value	Remarks			
			mg/l	ppm	mg/kg	others	
Triacetoxyethylsilane 17689-77-9	aqua (freshwater)		>= 0,2 mg/l				
Triacetoxyethylsilane 17689-77-9	aqua (marine water)		>= 0,02 mg/l				
Triacetoxyethylsilane 17689-77-9	aqua (intermittent releases)		1,7 mg/l				
Triacetoxyethylsilane 17689-77-9	sediment (freshwater)				>= 0,16 mg/kg		
Triacetoxyethylsilane 17689-77-9	sediment (marine water)				>= 0,016 mg/kg		
Triacetoxyethylsilane 17689-77-9	Soil				>= 0,031 mg/kg		
Triacetoxyethylsilane 17689-77-9	sewage treatment plant (STP)		> 1 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	aqua (freshwater)		0,0015 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	aqua (marine water)		0,00015 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	sewage treatment plant (STP)		10 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	sediment (freshwater)				3 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	sediment (marine water)				0,3 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	oral				41 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	Soil				0,84 mg/kg		

## **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Triacetoxyethylsilane 17689-77-9	Workers	inhalation	Long term exposure - local effects		32,5 mg/m3	
Triacetoxyethylsilane 17689-77-9	Workers	inhalation	Acute/short term exposure - local effects		32,5 mg/m3	
Triacetoxyethylsilane 17689-77-9	General population	inhalation	Long term exposure - local effects		6,5 mg/m3	
Triacetoxyethylsilane 17689-77-9	General population	inhalation	Long term exposure - systemic effects		19,81 mg/m3	
Triacetoxyethylsilane 17689-77-9	General population	dermal	Long term exposure - systemic effects		5,7 mg/kg	
Triacetoxyethylsilane 17689-77-9	General population	oral	Long term exposure - systemic effects		5,7 mg/kg	
Triacetoxyethylsilane 17689-77-9	Workers	inhalation	Long term exposure - systemic effects		80,33 mg/m3	
Triacetoxyethylsilane 17689-77-9	Workers	dermal	Long term exposure - systemic effects		11,39 mg/kg	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - systemic effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - local effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - systemic effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - local effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Long term exposure - systemic effects		3,7 mg/kg	

## **Biological Exposure Indices:**

None

## 8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	red
Odor	Acetic acid
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< -40 °C (< -40 °F)
Initial boiling point	>100 °C (>212 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	$> 100 \degree C (> 212 \degree F)$
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic
	peroxide and does not decompose under foreseen conditions of use
рН	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	> 20.5 mm2/s
(40 °C (104 °F); )	
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	< 0,1 hPa
(20 °C (68 °F))	,
Density	1,05 g/cm3 no method / method unknown
(20 °C (68 °F))	
Relative vapour density:	>1
(20 °C)	
Particle characteristics	Not applicable
	Product is a liquid

Other information not applicable for this product

9.2. Other information

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Reacts with oxidants, acids and lyes

### **10.2.** Chemical stability

Stable under recommended storage conditions.

# **10.3.** Possibility of hazardous reactions

See section reactivity

## 10.4. Conditions to avoid

Stable under normal conditions of storage and use. Excessive heat.

# **10.5.** Incompatible materials

See section reactivity.

# 10.6. Hazardous decomposition products

None if used for intended purpose.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Triacetoxyethylsilane 17689-77-9	LD50	1.460 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
octamethylcyclotetrasilox	LD50	> 4.800 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
ane				Toxicity)
556-67-2				

### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
octamethylcyclotetrasilox	LD50	> 2.375 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
ane				Dermal Toxicity)
556-67-2				

## Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
octamethylcyclotetrasilox	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
ane						Inhalation Toxicity)
556-67-2						

### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Triacetoxyethylsilane 17689-77-9	Category 1B (corrosive)	3 min	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
octamethylcyclotetrasilox ane 556-67-2	not irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

## Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
ane				Irritation / Corrosion)
556-67-2				

## Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Triacetoxyethylsilane 17689-77-9	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
octamethylcyclotetrasilox ane 556-67-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

## Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Triacetoxyethylsilane 17689-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Triacetoxyethylsilane 17689-77-9	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Triacetoxyethylsilane 17689-77-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
octamethylcyclotetrasilox ane 556-67-2	negative	bacterial gene mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
octamethylcyclotetrasilox ane 556-67-2	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
octamethylcyclotetrasilox ane 556-67-2	negative	inhalation		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

## Carcinogenicity

No data available.

## **Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
octamethylcyclotetrasilox ane	NOAEL P 300 ppm	two- generation	inhalation	rat	equivalent or similar to OECD Guideline 416 (Two-
556-67-2	NOAEL F1 300 ppm	study			Generation Reproduction Toxicity Study)

## STOT-single exposure:

No data available.

## STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Route of	Exposure time /	Species	Method
CAS-No.		application	Frequency of		
			treatment		
octamethylcyclotetrasilox	LOAEL 35 ppm	inhalation	6 h nose only	rat	OECD Guideline 412
ane			inhalation		(Repeated Dose
556-67-2			5 days/week for 13		Inhalation Toxicity:
			weeks		28/14-Day)
octamethylcyclotetrasilox	NOAEL 960 mg/kg	dermal	3 w	rabbit	equivalent or similar to
ane			5 d/w		OECD Guideline 410
556-67-2					(Repeated Dose Dermal
					Toxicity: 21/28-Day
					Study)

## Aspiration hazard:

No data available.

### 11.2 Information on other hazards

not applicable

## **SECTION 12: Ecological information**

## General ecological information:

Do not empty into drains / surface water / ground water. Self-classification according to Article 12(b) of (EU) 1272/2008.

### 12.1. Toxicity

### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Triacetoxyethylsilane	LC50	251 mg/l	96 h	Brachydanio rerio (new name:	OECD Guideline 203 (Fish,
17689-77-9				Danio rerio)	Acute Toxicity Test)
octamethylcyclotetrasiloxane	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name:	EPA OPPTS 797.1600 (Fish
556-67-2				Oncorhynchus mykiss)	Early Life Stage Toxicity
					Test)
octamethylcyclotetrasiloxane	LC50	Toxicity > Water	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish
556-67-2		solubility			Acute Toxicity Test)

### Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Triacetoxyethylsilane	EC50	168,7 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute
17689-77-9		-			Toxicity for Daphnia)
octamethylcyclotetrasiloxane	EC50	Toxicity > Water	48 h	Daphnia magna	EPA OTS 797.1300
556-67-2		solubility			(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater
					Daphnids)

### Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Triacetoxyethylsilane 17689-77-9	NOEC	>= 100 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)
octamethylcyclotetrasiloxane 556-67-2	NOEC	7.9 μg/l	21 d	· · · · · · · · · · · · · · · · · · ·	EPA OTS 797.1330 (Daphnid Chronic Toxicity Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Triacetoxyethylsilane 17689-77-9	EC50	> 1.562,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Triacetoxyethylsilane 17689-77-9	NOEC	40 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
octamethylcyclotetrasiloxane 556-67-2	EC10	0,022 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)

## Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	3 h	C	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)

### 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Triacetoxyethylsilane 17689-77-9	readily biodegradable	aerobic	74 %	21 d	EU Method C.4-A (Determination of the "Ready" BiodegradabilityDissolved Organic Carbon (DOC) Die-Away Test)
octamethylcyclotetrasiloxane 556-67-2	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

## 12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
octamethylcyclotetrasiloxane 556-67-2	12.400	28 d		Pimephales promelas	EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow
				1	Trout)

### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Triacetoxyethylsilane 17689-77-9	0,74		not specified
octamethylcyclotetrasiloxane 556-67-2	6,98	21,7 °C	other guideline:

### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Triacetoxyethylsilane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
17689-77-9	Bioaccumulative (vPvB) criteria.
octamethylcyclotetrasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
556-67-2	Bioaccumulative (vPvB) criteria.

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water. Dispose of in accordance with local and national regulations.

### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information		
14.1.	UN number or ID number	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.2.	UN proper shipping name	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.3.	Transport hazard class(es)	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.4.	Packing group	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.5.	Environmental hazards	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.6.	Special precautions for user	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.7.	Maritime transport in bulk according to IMO instruments	
	not applicable	

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture			
Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):		Not applicable	
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):		Not applicable	
Persistent organic pollutants (Regulation (EU) 2019/1021):		Not applicable	
VOC content	< 5 %		
(2010/75/EC)			

# 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## National regulations/information (Germany):

WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV) ) Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 10

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text
of all abbreviations indicated by codes in this safety data sheet are as follows:
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.